

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

AMPERE PROFESSIONAL PAINT all color

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Spray paints for professional use in aerosol containers

### 1.3. Details of the supplier of the safety data sheet

Company name: a.m.p.e.r.e. system sas  
Street: Boite postale 27526  
Place: F-95040 Cergy Pontoise Cedex  
Telephone: +33134647272  
Telefax: +33130375517  
e-mail: fds@amperesystem.com  
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

### 1.4. Emergency telephone

**number:** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24  
24

---

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

### 2.2. Label elements

#### Hazardous components which must be listed on the label

Acetone

Signal word:

Danger

Pictograms:



#### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

#### Precautionary statements

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P261 Avoid breathing spray.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical advice/attention.

**Safety Data Sheet** according to Regulation (EC) No 1907/2006

a.m.p.e.r.e. system sas

**AMPERE PROFESSIONAL PAINT all color**

Revision date: 26.06.2015

Revision No: 2,1

Product code: 00127-0081-GHS

---

P304+P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312

Call a POISON CENTER/doctor if you feel unwell.

**Special labelling of certain mixtures**

EUH066

Repeated exposure may cause skin dryness or cracking.

EUH208

Contains 2-ethylhexanoic acid, zirconium salt, 2-Butanone oxime. May produce an allergic reaction.

For professional users only

**2.3. Other hazards**

In use, may form flammable/explosive vapour-air mixture.

---

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Coloured synthetic resin aerosol in organic solvents

**AMPERE PROFESSIONAL PAINT all color**

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
67-64-1	Acetone			< 25 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
74-98-6	Propane			< 20 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1; H220			
106-97-8	Butane			< 10 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1; H220			
2807-30-9	2-(Propyloxy)ethanol			< 10 %
	220-548-6	603-095-00-2	01-2119883539-19	
	Flam. Liq. 3, Acute Tox. 4, Eye Irrit. 2; H226 H312 H319			
108-10-1	4-Methylpentan-2-one			< 10 %
	203-550-1	606-004-00-4	01-2119473980-30	
	Flam. Liq. 2, Acute Tox. 4, Eye Irrit. 2, STOT SE 3; H225 H332 H319 H335 EUH066			
110-19-0	Isobutyl acetate			< 5 %
	203-745-1	607-026-00-7	01-2119488971-22	
	Flam. Liq. 2; H225 EUH066			
108-65-6	2-Methoxy-1-methylethyl acetate			< 5 %
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3; H226			
107-87-9	isobutyl ketone			< 5 %
	203-528-1		01-2119988840-24	
	Flam. Liq. 2, Acute Tox. 4, Eye Irrit. 2; H225 H302 H319			
1330-20-7	Xylene (mixed isomers)			< 5 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H312 H332 H315 H319 H335 H373 H304			
22464-99-9	2-ethylhexanoic acid, zirconium salt			< 1 %
	245-018-1			
	Repr. 2, Resp. Sens. 1, Skin Sens. 1; H361d H334 H317			
96-29-7	2-Butanone oxime			< 1 %
	202-496-6	616-014-00-0	01-2119539477-28	
	Carc. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1; H351 H312 H318 H317			
64742-49-0	Naphtha (petroleum)			< 1 %
	921-024-6	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			

Full text of H and EUH phrases: see section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Remove contaminated soaked clothing immediately.

Take away from danger area and lay down affected person.

**AMPERE PROFESSIONAL PAINT all color**

Revision date: 26.06.2015

Revision No: 2,1

Product code: 00127-0081-GHS

---

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours.  
In the event of symptoms refer for medical treatment.

**After contact with skin**

Wash off with soap and plenty of water.  
Consult a doctor if skin irritation persists.

**After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.

**After ingestion**

Do not induce vomiting.  
Rinse out mouth and give plenty of water to drink.  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.

**4.2. Most important symptoms and effects, both acute and delayed**

Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.  
Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

---

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

**Unsuitable extinguishing media**

Full water jet.

**5.2. Special hazards arising from the substance or mixture**

Fire may produce:  
Carbon monoxide and carbon dioxide

**5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.  
Protective suit.

**Additional information**

Heating will cause pressure rise with risk of bursting.  
Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.  
Use only explosion-proof equipment.  
Ensure adequate ventilation.  
Use personal protective clothing.  
Keep away sources of ignition.

**6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.  
Do not discharge into the subsoil/soil.

**6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.

**6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

---

**AMPERE PROFESSIONAL PAINT all color**

Revision date: 26.06.2015

Revision No: 2,1

Product code: 00127-0081-GHS

Information for disposal see section 13.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Do not spray on a naked flame or any other incandescent material.

Heating will cause pressure rise with risk of bursting.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place.

**Advice on storage compatibility**

Incompatible with oxidizing agents.

**Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

**7.3. Specific end use(s)**

Spray paints for professional use in aerosol containers

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
108-10-1	4-Methylpentan-2-one	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
110-19-0	Isobutyl acetate	150	724		TWA (8 h)	WEL
		187	903		STEL (15 min)	WEL
107-87-9	Pentan-2-one	200	716		TWA (8 h)	WEL
		250	895		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-10-1	4-methylpentan-2-one	4-methylpentan-2-one	20 µmol/L	urine	Post shift
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

**8.2. Exposure controls**

**Protective and hygiene measures**

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

**AMPERE PROFESSIONAL PAINT all color**

Revision date: 26.06.2015

Revision No: 2,1

Product code: 00127-0081-GHS

---

Remove and wash contaminated clothes before re-use.

Avoid contact with eyes, skin or mucous membrane.

**Eye/face protection**

Safety goggles with side protection (EN 166).

Eye wash bottle with pure water (EN 15154).

**Hand protection**

Splash protection:

Protective gloves resistant to chemicals made off nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 30 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Long sleeved clothing (EN 368).

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type AX) (EN 14387).

---

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	Various
Odour:	Aromatic

**Changes in the physical state**

Initial boiling point and boiling range:	- 44 °C
Flash point:	- 19 °C
Lower explosion limits:	1,7 vol. %
Upper explosion limits:	10,9vol. %
Ignition temperature:	> 230 °C
Vapour pressure: (at 20 °C)	8300 hPa
Density (at 20 °C):	0,81 - 0,87 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	Slightly miscible
Solvent content:	< 60 %

**9.2. Other information**

No data available.

---

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with oxidizing agents.

**10.4. Conditions to avoid**

Fire or intense heat may cause violent rupture of packages.

In use formation of flammable/explosive vapour-air mixtures possible.

**10.5. Incompatible materials**

Strong oxidizing agents.

**10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

---

---

## **SECTION 11: Toxicological information**

### **11.1. Information on toxicological effects**

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

#### **Irritation and corrosivity**

Causes serious eye irritation.

Skin irritation: Not classified.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

#### **STOT-single exposure**

May cause drowsiness or dizziness. (Acetone), (Naphtha (petroleum) )

#### **Severe effects after repeated or prolonged exposure**

Repeated exposure may cause skin dryness or cracking.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **Practical experience**

#### **Other observations**

Repeated exposure may cause skin dryness or cracking.

Components of the product may be absorbed into the body through the skin. (skin absorption).

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

---

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Ecological data are not available.

### **12.2. Persistence and degradability**

No data available.

### **12.3. Bioaccumulative potential**

No data available.

### **12.4. Mobility in soil**

No data available.

### **12.5. Results of PBT and vPvB assessment**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### **12.6. Other adverse effects**

Low hazard to waters.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

---

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

#### **Advice on disposal**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

#### **Waste disposal number of waste from residues/unused products**

**AMPERE PROFESSIONAL PAINT all color**

Revision date: 26.06.2015

Revision No: 2,1

Product code: 00127-0081-GHS

150111 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers  
Classified as hazardous waste.

**Contaminated packaging**

Offer empty spray cans to an established disposal company.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Limited quantity: 1 L / 30 kg  
Excepted quantity: E0  
Transport category: 2  
Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Limited quantity: 1 L / 30 kg  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Marine pollutant: No  
Limited quantity: 1 L / 30 kg  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS



**AMPERE PROFESSIONAL PAINT all color**

Revision date: 26.06.2015

Revision No: 2,1

Product code: 00127-0081-GHS

**14.3. Transport hazard class(es):** 2.1

**14.4. Packing group:** -

Hazard label: 2.1



Limited quantity Passenger: 30 kg G

Passenger LQ: Y203

Excepted quantity: E0

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

The transport takes place only in approved and appropriate packaging.

---

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

2004/42/EC (VOC): < 70 %

**National regulatory information**

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

Water contaminating class (D): 1 - slightly water contaminating

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

---

**SECTION 16: Other information**

**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

**AMPERE PROFESSIONAL PAINT all color**

Revision date: 26.06.2015

Revision No: 2,1

Product code: 00127-0081-GHS

---

**Relevant H- and EUH-phrases (Number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains 2-ethylhexanoic acid, zirconium salt, 2-Butanone oxime. May produce an allergic reaction.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*