

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 14.02.2017



Version: 2

Revision: 14.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Trig-a-cap Original Black**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU21 Consumer uses: Private households / general public / consumers
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Process category**
 PROC7 Industrial spraying
 PROC11 Non industrial spraying
- **Application of the substance / the mixture** Spray varnish
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 · A.M.P.E.R.E. SYSTEM
 · 3 Rue Antoine Balard - P.A. du Vert Galant
 · 95310 Saint-Ouen-l'Aumône - France
 · Tel: +33 1 34 64 72 72
 · Fax: +33 1 30 37 55 17
 · E-mail: fds@amperesystem.com
- **1.4 Emergency telephone number:** 0344 892 0111

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
- | | |
|---|--|
|  | GHS02 flame |
| Aerosol 1 | H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. |
- | | |
|---|---|
|  | GHS07 |
| Skin Irrit. 2 | H315 Causes skin irritation. |
| Eye Irrit. 2 | H319 Causes serious eye irritation. |
| STOT SE 3 | H336 May cause drowsiness or dizziness. |
| Asp. Tox. 1 | H304 May be fatal if swallowed and enters airways. |
| Aquatic Chronic 3 | H412 Harmful to aquatic life with long lasting effects. |

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

(Contd. on page 2)
GB

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 14.02.2017

Version: 2

Revision: 14.02.2017

Trade name: Trig-a-cap Original Black

(Contd. of page 1)

· Hazard statements

- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe spray.
 P211 Do not spray on an open flame or other ignition source.
 P280 Wear protective gloves / eye protection.
 P273 Avoid release to the environment.
 P271 Use only outdoors or in a well-ventilated area.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P403 Store in a well-ventilated place.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

- EUH208 Contains Fatty acids, C18-unsatd., trimers compds. with oleylamine, phthalic anhydride. May produce an allergic reaction.

· 2.3 Other hazards**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
 · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

- **Description:** Active substance with propellant

· Dangerous components:

CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas C, H280	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas C, H280	10-<25%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	10-<25%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10-<25%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<10%

(Contd. on page 3)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 14.02.2017

Version: 2

Revision: 14.02.2017

Trade name: Trig-a-cap Original Black

		(Contd. of page 2)
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene (mix) Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<10%
CAS: 1333-86-4 EINECS: 215-609-9	Carbon black Self-heat. 1, H251	0.1-<1.0%
· Ingredients according to detergents guideline 648/2004/EC		
aliphatic hydrocarbons		≥ 30%
aromatic hydrocarbons		< 5%
· Additional information:		

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

GB

(Contd. on page 4)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 14.02.2017

Version: 2

Revision: 14.02.2017

Trade name: Trig-a-cap Original Black

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Keep receptacle tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 propane

OEL	Short-term value: 3600 mg/m ³ , 2000 ppm
	Long-term value: 1800 mg/m ³ , 1000 ppm

141-78-6 ethyl acetate

WEL	Short-term value: 400 ppm
	Long-term value: 200 ppm

1330-20-7 xylene (mix)

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

1333-86-4 Carbon black

WEL	Short-term value: 7 mg/m ³
	Long-term value: 3.5 mg/m ³

· DNELs

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	DNEL Long term-systemic	125 mg/kg bw/day (Consumer)
Derma	DNEL Long term-systemic	125 mg/kg bw/day (Consumer)
		208 mg/kg bw/day (Worker)

(Contd. on page 5)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 14.02.2017

Version: 2

Revision: 14.02.2017

Trade name: Trig-a-cap Original Black

(Contd. of page 4)

Inhalative	DNEL Long term-systemic	185 mg/m ³ (Consumer) 871 mg/m ³ (Worker)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer) 773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m ³ (Consumer) 2035 mg/m ³ (Worker)
141-78-6 ethyl acetate		
Oral	DNEL Long term-systemic	4.5 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	37 mg/kg bw/day (Consumer) 63 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-systemic	734 mg/m ³ (Consumer) 1468 mg/m ³ (Worker)
	DNEL Acute-local	734 mg/m ³ (Consumer) 1468 mg/m ³ (Worker)
	DNEL Long term-systemic	367 mg/m ³ (Consumer) 34 mg/m ³ (Worker)
	DNEL Long term-local	367 mg/m ³ (Consumer) 734 mg/m ³ (Worker)
· PNECs		
141-78-6 ethyl acetate		
PNEC Freshwater		0.26 mg/l (Undefined)
PNEC Marine water		0.026 mg/l (Undefined)
PNEC Freshwater sediment		0.34 mg/kg (Undefined)
PNEC Soil		0.22 mg/kg (Undefined)
PNEC Sewage Treatment Plant		650 mg/l (Undefined)
PNEC Marine water sediment		0.034 mg/kg (Undefined)
· Ingredients with biological limit values:		
1330-20-7 xylene (mix)		
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid	
· Additional Occupational Exposure Limit Values for possible hazards during processing:		
100-41-4 ethylbenzene		
WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk	
108-88-3 toluene		
WEL	Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk	

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

(Contd. on page 6)

GB

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 14.02.2017

Version: 2

Revision: 14.02.2017

Trade name: Trig-a-cap Original Black

(Contd. of page 5)

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· Protection of hands:

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm**· Penetration time of glove material**

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

· Body protection: Use protective suit. (EN-13034/6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties**· General Information****· Appearance:****Form:** Aerosol**Colour:** Black**· Odour:** Characteristic**· Odour threshold:** Not determined.**· pH-value:** Not determined.**· Change in condition****Melting point/freezing point:** Undetermined.**Initial boiling point and boiling range:** -44 °C**· Flash point:** -97 °C

(Contd. on page 7)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 14.02.2017

Version: 2

Revision: 14.02.2017

Trade name: Trig-a-cap Original Black

(Contd. of page 6)

· Flammability (solid, gas):	Not applicable.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	11.5 Vol %
· Vapour pressure at 20 °C:	4 bar
· Density at 20 °C:	0.7 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	81.8 %
Solids content:	18.3 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 (4h)	4951 mg/m ³ (rat)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rabbit)
Inhalative	LC50/4h	>25 mg/l (rat)

(Contd. on page 8)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 14.02.2017

Version: 2

Revision: 14.02.2017

Trade name: Trig-a-cap Original Black

(Contd. of page 7)

141-78-6 ethyl acetate

Oral	LD50	4100 mg/kg (mouse)
Inhalative	LC50/4 h	1600 mg/l (rat)

1330-20-7 xylene (mix)

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information· **12.1 Toxicity**· **Aquatic toxicity:****Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**

EL0 (48h)	1000 mg/l (Daphnia magna)
NOELR (72h)	100 mg/l (Pseudokirchneriella subcapitata)
EL50 (72h)	>1000 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	>1000 mg/l (Oncorhynchus mykiss (96h))

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

NOELR (72h)	3 mg/l (Pseudokirchneriella subcapitata)
EL50(48h)	3 mg/l (Daphnia magna)
EL50 (72h)	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	11.4 mg/l (Oncorhynchus mykiss (96h))
NOEC (21 days)	0.17 mg/l (Daphnia magna)
LOEC (21 days)	0.32 mg/l (Daphnia magna)

141-78-6 ethyl acetate

EC50/48h	0.164 mg/l (Daphnia magna) 3.3 mg/l (Scenedesmus subspicatus)
EC50	7.4 mg/l (Pseudomonas fluorescens)

1330-20-7 xylene (mix)

LC50/96h	8.9-16.4 mg/l (Pimephales promelas)
EC50/48h	3.2-9.5 mg/l (Daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish

(Contd. on page 9)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 14.02.2017

Version: 2

Revision: 14.02.2017

Trade name: Trig-a-cap Original Black



(Contd. of page 8)

- **Additional ecological information:**
- **General notes:**
 - Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
 - Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 - Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|--|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, ADN, IMDG, IATA | UN1950 |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR, ADN · IMDG · IATA | UN1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR <div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label | 2 5F Gases.
2.1 |
| <ul style="list-style-type: none"> · ADN · ADN/R Class: | 2 5F |
| <ul style="list-style-type: none"> · IMDG, IATA <div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label | 2.1
2.1 |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | Void |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | No |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): | Warning: Gases.
- |

(Contd. on page 10)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 14.02.2017

Version: 2

Revision: 14.02.2017

Trade name: Trig-a-cap Original Black

(Contd. of page 9)

· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

Class	Share in %
NK	75-<100

- **VOC-CH** 81.58 %
- **VOC-EU** 572.9 g/l
- **Danish MAL Code** 5-3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.

(Contd. on page 11)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 14.02.2017

Version: 2

Revision: 14.02.2017

Trade name: Trig-a-cap Original Black

(Contd. of page 10)

H251 Self-heating: may catch fire.
 H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1: Flammable gases – Category 1
 Aerosol 1: Aerosols – Category 1
 Press. Gas C: Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Self-heat. 1: Self-heating substances and mixtures – Category 1
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB