

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trig-a-cap Water Based²

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Spray paints for professional use in aerosol containers

1.3. Details of the supplier of the safety data sheet

Company name: A.M.P.E.R.E. System SAS
Street: Boite postale 27526
Place: F-95040 Cergy Pontoise Cedex
Telephone: +33134647272
Telefax: +33130375517
e-mail: fds@amperesystem.com
0344 892 0111

1.4. Emergency telephone number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects .

2.2. Label elements

Signal word:

Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P261 Avoid breathing spray.

P302+P352 IF ON SKIN: Wash with plenty of water.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P273 Avoid release to the environment.

Special labelling of certain mixtures

For professional users only

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

In use, may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Coloured synthetic resin aerosol in organic solvents

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
74-98-6	Propane			< 20 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Compressed gas; H220 H280			
64742-49-0	Naphtha (petroleum)			< 20 %
	265-151-9			
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
106-97-8	Butane			< 15 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Compressed gas; H220 H280			
1330-20-7	Xylene (mixed isomers)			< 10 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
110-19-0	Isobutyl acetate			< 5 %
	203-745-1	607-026-00-7	01-2119488971-22	
	Flam. Liq. 2, STOT SE 3; H225 H336 EUH066			
100-41-4	Ethyl benzene			< 5 %
	202-849-4	601-023-00-4	02-2119752523-40	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			

Full text of H and EUH statements: see section 16.

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphtha (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

According to note P to the regulation (EC) no. 1272/2008, "distillate (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
Take away from danger area and lay down affected person .

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off with soap and plenty of water.
Treat subsequently with skin cream.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.

After ingestion

Induce vomiting only upon the advice of a physician.
Do not induce vomiting.
Summon a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.
May cause drowsiness or dizziness.
Contact with eyes may cause irritation.
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.
Use only explosion-proof equipment.
Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.
Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.
Do not spray on a naked flame or any other incandescent material.
Heating will cause pressure rise with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Spray paints for professional use in aerosol containers

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
1317-65-3	Calcium carbonate, inhalable dust	-	10		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
110-19-0	Isobutyl acetate	150	724		TWA (8 h)	WEL
		187	903		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route	Effect	Value	
1317-65-3	calcium carbonate			
Worker DNEL, long-term	inhalation	systemic	10 mg/m ³	

PNEC values

CAS No	Substance		
Environmental compartment	Value		
1317-65-3	calcium carbonate		
Micro-organisms in sewage treatment plants (STP)	100 mg/l		

8.2. Exposure controls

Protective and hygiene measures

Wash hands before breaks and immediately after handling the product .
 When using do not eat, drink or smoke.
 Take off immediately all contaminated clothing.
 Avoid contact with eyes, skin or mucous membrane.

Eye/face protection

Safety goggles with side protection (EN 166).

Hand protection

Splash protection:

Protective gloves resistant to chemicals made off nitrile , minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 30 minutes, i.e. protective glove < Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type AX) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
 Colour: Different
 Odour: Solvent-like

Changes in the physical state

Initial boiling point and boiling range: - 44 °C
 Flash point: - 19 °C
 Lower explosion limits: 1,5 vol. %

Upper explosion limits:	10,9vol. %
Ignition temperature:	210 °C
Density (at 20 °C):	< 1 g/cm ³
Water solubility: (at 20 °C)	Immiscible
Solvent content:	< 35 %

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

Fire or intense heat may cause violent rupture of packages.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Contact with eyes may cause irritation.

Components of the product may be absorbed into the body through the skin. (skin absorption).

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects .

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

150111 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers; hazardous waste

Contaminated packaging

Offer empty spray cans to an established disposal company.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Limited quantity: 1 L / 30 kg
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2

14.4. Packing group: -

Hazard label: 2.1



Classification code: 5F

Limited quantity: 1 L / 30 kg

Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Hazard label: 2.1



Marine pollutant: No

Limited quantity: 1 L / 30 kg

Excepted quantity: E0

EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Hazard label: 2.1



Limited quantity Passenger: 30 kg G

Passenger LQ: Y203

Excepted quantity: E0

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): < 60 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our

Safety Data Sheet according to Regulation (EC) No 1907/2006

A.M.P.E.R.E. System SAS

Trig-a-cap Water Based²

Revision date: 22.11.2017

Revision No: 2,2

Product code: 00127-0059-GHS

knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)