

**AMPERE STAR MARKER**

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

AMPERE STAR MARKER

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Spray paints for professional use in aerosol containers

**1.3. Details of the supplier of the safety data sheet**

Company name: a.m.p.e.r.e. system sas  
Street: Boite postale 27526  
Place: F-95040 Cergy Pontoise Cedex  
Telephone: +33134647272  
Telefax: +33130375517  
e-mail: fds@amperesystem.com  
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**1.4. Emergency telephone**

**number:** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24  
24

---

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture according to 1272/2008/EC**

Hazard categories:  
Aerosol: Aerosol 1  
Skin corrosion/irritation: Skin Irrit. 2  
Specific target organ toxicity - single exposure: STOT SE 3  
Hazardous to the aquatic environment: Aquatic Chronic 3  
Hazard Statements:  
Extremely flammable aerosol.  
Pressurised container: May burst if heated.  
Causes skin irritation.  
May cause drowsiness or dizziness.  
Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

**Hazardous components which must be listed on the label**

Naphtha (petroleum)

Signal word: Danger

Pictograms:



**Hazard statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P261 Avoid breathing spray.

**AMPERE STAR MARKER**

Revision date: 26.06.2015

Revision No: 2,1

Product code: 00127-0074-GHS

P302+P352 IF ON SKIN: Wash with plenty of water.  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P312 Call a POISON CENTER/doctor if you feel unwell.  
 P273 Avoid release to the environment.

**Special labelling of certain mixtures**

For professional users only

**2.3. Other hazards**

In use, may form flammable/explosive vapour-air mixture.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Coloured synthetic resin aerosol in organic solvents

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
74-98-6	Propane			< 20 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1; H220			
64742-49-0	Naphtha (petroleum)			< 20 %
	921-024-6	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
106-97-8	Butane			< 15 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1; H220			
64742-47-8	Distillates (petroleum)			< 10 %
	265-149-8			
	Asp. Tox. 1; H304 EUH066			
110-19-0	Isobutyl acetate			< 10 %
	203-745-1	607-026-00-7	01-2119488971-22	
	Flam. Liq. 2; H225 EUH066			
68410-97-9	Distillates (petroleum)			< 1 %
	270-093-2		01-2119826256-38	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 4; H225 H315 H336 H304 H413			

Full text of H and EUH phrases: see section 16.

**Further information**

According to note P to the regulation (EC) no. 1272/2008, "Naphtha (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Remove contaminated soaked clothing immediately.  
 Take away from danger area and lay down affected person.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours.  
 In the event of symptoms refer for medical treatment.

**After contact with skin**

Wash off with soap and plenty of water.  
Treat subsequently with skin cream.  
Consult a doctor if skin irritation persists.

**After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
If eye irritation persists, consult a specialist.

**After ingestion**

Induce vomiting only upon the advice of a physician.  
Do not induce vomiting.  
Summon a doctor immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Causes skin irritation.  
May cause drowsiness or dizziness.  
Contact with eyes may cause irritation.  
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

---

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

**Unsuitable extinguishing media**

Full water jet.

**5.2. Special hazards arising from the substance or mixture**

Fire may produce:  
Carbon monoxide and carbon dioxide

**5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.  
Protective suit.

**Additional information**

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Cool containers at risk with water spray jet.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.  
Use only explosion-proof equipment.  
Ensure adequate ventilation.  
Use personal protective clothing.  
Keep away sources of ignition.

**6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.  
Do not discharge into the subsoil/soil.

**6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.

**6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).  
Information for disposal see section 13.

---

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**AMPERE STAR MARKER**

**Advice on safe handling**

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Do not spray on a naked flame or any other incandescent material.

Heating will cause pressure rise with risk of bursting.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep containers tightly closed in a cool, well-ventilated place.

**Advice on storage compatibility**

Incompatible with oxidizing agents.

**Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

**7.3. Specific end use(s)**

Spray paints for professional use in aerosol containers

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
1317-65-3	Calcium carbonate, respirable	-	4		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
110-19-0	Isobutyl acetate	150	724		TWA (8 h)	WEL
		187	903		STEL (15 min)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
1317-65-3	Calcium carbonate			
Worker DNEL, long-term		inhalation	systemic	10 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	systemic	10 mg/m <sup>3</sup>
Consumer DNEL, acute		dermal	systemic	6,1 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	6,1 mg/kg bw/day

**PNEC values**

CAS No	Substance	Value
Environmental compartment		
1317-65-3	Calcium carbonate	
Micro-organisms in sewage treatment plants (STP)		100 mg/l

**8.2. Exposure controls**

**Protective and hygiene measures**

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Take off immediately all contaminated clothing.

Avoid contact with eyes, skin or mucous membrane.

**Eye/face protection**

Safety goggles with side protection (EN 166).

**Hand protection**

Splash protection:

Protective gloves resistant to chemicals made off nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 30 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Long sleeved clothing (EN 368).

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type AX) (EN 14387).

---

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	Various
Odour:	Solvent-like

**Changes in the physical state**

Initial boiling point and boiling range:	- 44 °C
Flash point:	- 19 °C
Lower explosion limits:	1,5 vol. %
Upper explosion limits:	10,9vol. %
Ignition temperature:	210 °C
Density (at 20 °C):	n.d.
Water solubility: (at 20 °C)	Immiscible
Solvent content:	< 25 %

**9.2. Other information**

No data available.

---

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with oxidizing agents.

**10.4. Conditions to avoid**

Fire or intense heat may cause violent rupture of packages.

In use formation of flammable/explosive vapour-air mixtures possible.

**10.5. Incompatible materials**

Strong oxidizing agents.

**10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

---

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Acute toxicity**

Based on available data, the classification criteria are not met.  
No toxicological data available.

**Irritation and corrosivity**

Causes skin irritation.  
Eye irritation: Not classified.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Naphtha (petroleum) ), (Distillates (petroleum) )

**Severe effects after repeated or prolonged exposure**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

**Practical experience**

**Other observations**

Contact with eyes may cause irritation.  
Components of the product may be absorbed into the body through the skin. (skin absorption).  
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

---

**SECTION 12: Ecological information**

**12.1. Toxicity**

Ecological data are not available.  
Harmful to aquatic life with long lasting effects.

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

**12.6. Other adverse effects**

Low hazard to waters.

**Further information**

Do not flush into surface water or sanitary sewer system.

---

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Advice on disposal**

Where possible recycling is preferred to disposal.  
Can be incinerated, when in compliance with local regulations.

**Waste disposal number of waste from residues/unused products**

**AMPERE STAR MARKER**

Revision date: 26.06.2015

Revision No: 2,1

Product code: 00127-0074-GHS

150111 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers  
Classified as hazardous waste.

**Contaminated packaging**

Offer empty spray cans to an established disposal company.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Limited quantity: 1 L /30 kg  
Excepted quantity: E0  
Transport category: 2  
Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2.1



Classification code: 5F  
Limited quantity: 1 L /30 kg  
Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
Hazard label: 2.1



Marine pollutant: No  
Limited quantity: 1 L /30 kg  
Excepted quantity: E0  
EmS: F-D, S-U

**Air transport (ICAO)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS

**AMPERE STAR MARKER**

Revision date: 26.06.2015

Revision No: 2,1

Product code: 00127-0074-GHS

**14.3. Transport hazard class(es):** 2.1

**14.4. Packing group:** -

Hazard label: 2.1



Limited quantity Passenger: 30 kg G

Passenger LQ: Y203

Excepted quantity: E0

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

The transport takes place only in approved and appropriate packaging.

---

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

2004/42/EC (VOC): < 50 %

**National regulatory information**

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

Water contaminating class (D): 1 - slightly water contaminating

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

---

**SECTION 16: Other information**

**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration



**AMPERE STAR MARKER**

**Relevant H- and EUH-phrases (Number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*