Safety Data Sheet according to Regulation (EC) No 1907/2006 a.m.p.e.r.e. systemsas AMPERE trig-a-cap water based / AMPERE STAR MARKER Revision date: 26.06.2015 Revision No: 2,1 Product code: 00127-0074-GHS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

AMPERE trig-a-cap water based / AMPERE STAR MARKER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Spray paints for professional use in aerosol containers

1.3. Details of the supplier of the safety data sheet

Company name:	a.m.p.e.r.e. system sas
Street:	Boite postale 27526
Place:	F-95040 Cergy Pontoise Cedex
Telephone:	+33134647272
Telefax:	+33130375517
e-mail:	fds@amperesystem.com
Responsible Department:	Responsible for the safety data sheet: sds@gbk-ingelheim.de
<u>1.4. Emergency telephone</u> number:	INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24 - 0344 892 0111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories: Aerosol: Aerosol 1 Skin corrosion/irritation: Skin Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazardous components which must be listed on the label Naphtha (petroleum)

Signal word:

Pictograms:



Danger

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
Precautionary sta	tements
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P261	Avoid breathing spray.

AMPERE trig-a-cap water based / AMPERE STAR MARKER

Revision date: 26.06.2015 Revision No: 2,1 Product code: 00127-0074-GHS

· · · · · ·	
P273	Avoid release to the environment.
P312	Call a POISON CENTER/doctor if you feel unwell.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water.

Special labelling of certain mixtures

For professional users only

2.3. Other hazards

In use, may form flammable/explosive vapour-airmixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Coloured synthetic resin aerosol in organic solvents

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regula	CLP]		
74-98-6	Propane			< 20 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1; H220	-		
64742-49-0	Naphtha (petroleum)			< 20 %
	921-024-6	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE H411			
106-97-8	-8 Butane			< 15 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1; H220			
64742-47-8	Distillates (petroleum)			< 10 %
	265-149-8			
	Asp. Tox. 1; H304 EUH066			
110-19-0	Isobutyl acetate			< 10 %
	203-745-1	607-026-00-7	01-2119488971-22	
	Flam. Liq. 2; H225 EUH066			
68410-97-9	Distillates (petroleum)			< 1 %
	270-093-2		01-2119826256-38	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 4; H225 H315 H336 H413			

Full text of H and EUH phrases: see section 16.

FurtherInformation

According to note P to the regulation (EC) no. 1272/2008, "Naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately. Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours. In the event of symptoms refer for medical treatment.

Safety Data Sheet according to Regulation (EC) No 1907/2006 a.m.p.e.r.e. systemsas

AMPERE trig-a-cap water based / AMPERE STAR MARKER

Revision date: 26.06.2015 Revision No: 2,1 Product code: 00127-0074-GHS

After contact with skin

Wash off with soap and plenty of water. Treat subsequently with skin cream. Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

After ingestion

Induce vomiting only upon the advice of a physician. Do not induce vomiting. Summon a doctorimmediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

May cause drowsiness or dizziness.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce: Carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply. Protective suit.

Additional information

The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers at risk with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator. Use only explosion-proof equipment. Ensure adequate ventilation. Use personal protective clothing. Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container fordisposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safety Data Sheet according to Regulation (EC) No 1907/2006 a.m.p.e.r.e. system sas

AMPERE trig-a-cap water based / AMPERE STAR MARKER

Revision date: 26.06.2015 Revision No: 2,1 Product code: 00127-0074-GHS

Advice on safe handling

Ensure adequate ventilation. Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Do not spray on a naked flame or any other incandescent material. Heating will cause pressure rise with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific enduse(s)

Spray paints for professional use in aerosol containers

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits(EH40)

Substance	ppm	mg/m³	fibres/ml	Category	Origin
Butane	600	1450		TWA (8 h)	WEL
	750	1810		STEL (15 min)	WEL
Calcium carbonate, respirable	-	4		TWA (8 h)	WEL
	-	-		STEL (15 min)	WEL
Isobutyl acetate	150	724		TWA (8 h)	WEL
	187	903		STEL (15 min)	WEL
	Butane Calcium carbonate, respirable	Butane 600 Calcium carbonate, respirable - Isobutyl acetate 150	Butane 600 1450 Calcium carbonate, respirable - 4 Isobutyl acetate 150 724	Butane6001450Calcium carbonate, respirable-4Isobutyl acetate150724	Butane 600 1450 TWA (8 h) Calcium carbonate, respirable - 4 TWA (8 h) Isobutyl acetate 150 724 TWA (8 h)

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1317-65-3	Calcium carbonate			
Worker DNEL,	long-term	inhalation	systemic	10 mg/m ³
Consumer DNE	EL, long-term	inhalation	systemic	10 mg/m ³
Consumer DNEL, acute		dermal	systemic	6,1 mg/kg bw/day
Consumer DNE	EL, long-term	dermal	systemic	6,1 mg/kg bw/day

PNEC values

CAS No Substance		
Environmental	compartment	Value
1317-65-3 Calcium carbonate		
Micro-organisms in sewage treatment plants (STP) 100 mg/l		

8.2. Exposure controls

Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Take off immediately all contaminated clothing.

Avoid contact with eyes, skin or mucous membrane.

Safety Data Sheet according to Regulation (EC) No 1907/2006 a.m.p.e.r.e. systemsas

AMPERE trig-a-cap water based / AMPERE STAR MARKER

Revision date: 26.06.2015 Revision No: 2,1 Product code: 00127-0074-GHS

Eye/faceprotection

Safety goggles with side protection (EN 166).

Hand protection

Splash protection:

Protective gloves resistant to chemicals made off nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 30 minutes, i.e. protective glove < Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type AX) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	Aerosol Various
Odour:	Solvent-like
Changes in the physical state	
Initial boiling point and boiling range:	- 44 °C
Flash point:	- 19 °C
Lower explosion limits:	1,5 vol. %
Upper explosion limits:	10,9vol. %
Ignition temperature:	210 °C
Density (at 20 °C):	nd

Density (at 20 °C):	n.d.
Water solubility:	Immiscible
(at 20 °C)	
Solvent content:	< 25 %
9.2. Other information	

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

Fire or intense heat may cause violent rupture of packages. In use formation of flammable/explosive vapour-air mixtures possible.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Safety Data Sheet according to Regulation (EC) No 1907/2006 a.m.p.e.r.e. systemsas

AMPERE trig-a-cap water based / AMPERE STAR MARKER

Revision date: 26.06.2015 Revision No: 2,1 Product code: 00127-0074-GHS

Acutetoxicity

Based on available data, the classification criteria are not met. No toxicological data available.

Irritation and corrosivity

Causes skin irritation. Eye irritation: Not classified.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum)), (Distillates (petroleum))

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Otherobservations

Contact with eyes may cause irritation.

Components of the product may be absorbed into the body through the skin. (skin absorption). Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are notavailable. Harmful to aquatic life with long lasting effects. <u>12.2.</u> **Persistence and degradability** No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal. Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

Safety Data Sheet according to Regulation (EC) No 1907/2006 a.m.p.e.r.e. systemsas AMPERE trig-a-cap water based / AMPERE STAR MARKER

•	
Revision date: 26.06.2015	Revision No: 2,1
Product code: 00127-0074-GHS	

150111 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers Classified as hazardous waste.

Contaminated packaging

Offer empty spray cans to an established disposal company.

SECTION 14: Transport information

Land transport (ADR/RID)	
<u>14.1. UN number:</u>	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packinggroup:	-
Hazard label:	2.1
Classification code:	5F
Limited quantity:	1 L /30 kg
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
	2
Classification code:	2 5F
Limited quantity:	1 L /30 kg
Limited quantity: Excepted quantity:	•••
Limited quantity:	1 L /30 kg
Limited quantity: Excepted quantity:	1 L /30 kg
Limited quantity: Excepted quantity: Marine transport (IMDG)	1 L /30 kg E0
Limited quantity: Excepted quantity: Marine transport (IMDG) 14.1. UN number:	1 L /30 kg E0 UN 1950
Limited quantity: Excepted quantity: Marine transport (IMDG) 14.1. UN number: 14.2. UN proper shipping name:	1 L /30 kg E0 UN 1950 AEROSOLS
Limited quantity: Excepted quantity: Marine transport (IMDG) 14.1. UN number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es):	1 L /30 kg E0 UN 1950 AEROSOLS
Limited quantity: Excepted quantity: Marine transport (IMDG) 14.1. UN number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packinggroup:	1 L /30 kg E0 UN 1950 AEROSOLS 2.1
Limited quantity: Excepted quantity: Marine transport (IMDG) 14.1. UN number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packinggroup: Hazard label: Marine pollutant:	1 L /30 kg E0 UN 1950 AEROSOLS 2.1 - 2.1 - 2.1 No
Limited quantity: Excepted quantity: Marine transport (IMDG) 14.1. UN number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packinggroup: Hazard label: Marine pollutant: Limited quantity:	1 L /30 kg E0 UN 1950 AEROSOLS 2.1 - 2.1 V 0 No 1 L /30 kg
Limited quantity: Excepted quantity: Marine transport (IMDG) 14.1. UN number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packinggroup: Hazard label: Marine pollutant: Limited quantity: Excepted quantity:	1 L /30 kg E0 UN 1950 AEROSOLS 2.1 - 2.1 - 2.1 No 1 L /30 kg E0
Limited quantity: Excepted quantity: Marine transport (IMDG) 14.1. UN number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packinggroup: Hazard label: Marine pollutant: Limited quantity: Excepted quantity: Excepted quantity: EmS:	1 L /30 kg E0 UN 1950 AEROSOLS 2.1 - 2.1 V 0 No 1 L /30 kg
Limited quantity: Excepted quantity: Marine transport (IMDG) 14.1. UN number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packinggroup: Hazard label: Hazard label: Marine pollutant: Limited quantity: Excepted quantity: Excepted quantity: EmS: Air transport (ICAO)	1 L /30 kg E0 UN 1950 AEROSOLS 2.1 - 2.1 V 2.1 V 0 1 L /30 kg E0 F-D, S-U
Limited quantity: Excepted quantity: Marine transport (IMDG) 14.1. UN number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packinggroup: Hazard label: Marine pollutant: Limited quantity: Excepted quantity: Excepted quantity: EmS:	1 L /30 kg E0 UN 1950 AEROSOLS 2.1 - 2.1 - 2.1 No 1 L /30 kg E0

Safety Data Sheet according to Regulation (EC) No 1907/2006 a.m.p.e.r.e. system sas

AMPERE trig-a-cap water based / AMPERE STAR MARKER

Revision date: 26.06.2015	Revision No: 2,1
Product code:00127-0074-GHS	

14.3. Transport hazard class(es):	2.1	
14.4. Packinggroup:	-	
Hazard label:	2.1	
Limited quantity Passenger:	30 kg G	
Passenger LQ:	Y203	
Excepted quantity:	E0	
IATA-packing instructions - Passenger:		203
IATA-max. quantity - Passenger:		75 kg
IATA-packing instructions - Cargo:		203
IATA-max. quantity - Cargo:		150 kg
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	no	

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

EU regulatory information		
2004/42/EC (VOC):	< 50 %	
National regulatory information		
Employment restrictions:	Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.	
Water contaminating class (D):	1 - slightly water contaminating	
15.2. Chemical safety assessment		
For this substance a chemical safety assessment has not been carried out.		

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical AbstractService

EN = European norm

- ISO = International Organization for Standardization
- DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

 $\label{eq:IC} \mbox{IC} = \mbox{Median immobilisation concentration or median inhibitory concentration}$

Safety Data Sheet according to Regulation (EC) No 1907/2006 a.m.p.e.r.e. system sas

AMPERE trig-a-cap water based / AMPERE STAR MARKER

Revision date: 26.06.2015 Revision No: 2,1 Product code: 00127-0074-GHS

Relevant H- and EUH-phrases (Number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of ourknowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)