

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** GRAFFITI REMOVER - PAINT REMOVER
- **Article number:** 632060000
- **UFI:** T4N5-00RV-Y00S-MESG
- **1.2 Relevant identified uses of the substance or mixture and uses advised against -**
- **Application of the substance / the mixture** Surface cleaning
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
A.M.P.E.R.E. SYSTEM
3 rue Antoine Balard - Z.I. du Vert Galant
95310 Saint-Ouen-l'Aumône - FRANCE
Tél: + 33 1 34 64 72 72 / Fax: +33 1 30 37 55 17
- **Further information obtainable from:** fds@amperesystem.com
- **1.4 Emergency telephone number:** UK : National Poisons Information Service - 0344 892 0111
Ireland : National Poisons Information Centre - Beaumont Hospital - PO Box 1297 Beaumont Road 9 Dublin : +353 1 809 2566
(Healthcare professionals-24/7) - +353 1 809 2166 (public, 8am - 10pm, 7/7)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Danger
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

Trade name: GRAFFITI REMOVER - PAINT REMOVER

(Contd. of page 1)

- P260 Do not breathe mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves / eye protection.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

Determination of endocrine-disrupting properties

78-93-3	butanone	List II
95-14-7	benzotriazole	List II

SECTION 3: Composition/information on ingredients
3.2 Mixtures

- **Description:** Active substance with propellant

Dangerous components:

CAS: 109-87-5 EINECS: 203-714-2 Reg.nr.: 01-2119664781-31	methane, dimethoxy- Flam. Liq. 2, H225	50-<75%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 646-06-0 EINECS: 211-463-5 Reg.nr.: 01-2119490744-29-0004	1,3-dioxolane Flam. Liq. 2, H225; Eye Irrit. 2, H319	2.5-<10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<10%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	2.5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8), Note K) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<2.5%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	1-<2.5%
CAS: 141-43-5 EINECS: 205-483-3 Reg.nr.: 01-2119486455-28	2-aminoethanol Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limit: STOT SE 3; H335: C ≥ 5 %	1-<2.5%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1% Asp. Tox. 1, H304, EUH066	1-<2.5%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

Trade name: GRAFFITI REMOVER - PAINT REMOVER

(Contd. of page 2)

CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	0.1-<1%
CAS: 95-14-7 EINECS: 202-394-1 Reg.nr.: 01-2119979079-20	benzotriazole Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	≤0.1%

Ingredients according to detergents guideline 648/2004/EC

aliphatic hydrocarbons	≥15 - <30%
non-ionic surfactants	<5%

Additional information:

Aerosols and containers fitted with a solid atomizer containing substances or mixtures classified as hazardous by aspiration shall not be labelled for that hazard.

The text of the hazard statements mentioned here can be found in chapter 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

Trade name: GRAFFITI REMOVER - PAINT REMOVER

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:**
Observe official regulations on storing packagings with pressurised containers.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

109-87-5 methane, dimethoxy-

WEL	Short-term value: 3950 mg/m ³ , 1250 ppm
	Long-term value: 3160 mg/m ³ , 1000 ppm

74-98-6 propane

OEL	Long-term value: 1800 mg/m ³ , 1000 ppm
	Additioneel ingevuld tbv klant voor Hfdst3 SDS

646-06-0 1,3-dioxolane

OEL	Long-term value: 62 mg/m ³ , 20 ppm
-----	--

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm
	Long-term value: 999 mg/m ³ , 400 ppm

64-17-5 ethanol

WEL	Long-term value: 1920 mg/m ³ , 1000 ppm
-----	--

106-97-8 butane (containing < 0.1% butadiene (203-450-8), Note K)

WEL	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

78-93-3 butanone

WEL	Short-term value: 899 mg/m ³ , 300 ppm
	Long-term value: 600 mg/m ³ , 200 ppm
	Sk, BMGV

141-43-5 2-aminoethanol

WEL	Short-term value: 7.6 mg/m ³ , 3 ppm
	Long-term value: 2.5 mg/m ³ , 1 ppm
	Sk

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

Trade name: GRAFFITI REMOVER - PAINT REMOVER

(Contd. of page 4)

Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1%
OEL Short-term value: 1200 mg/m³, 184 ppm
75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K)
OEL Long-term value: 2400 mg/m³, 1000 ppm
Additioneel ingevuld obv klant voor Hfdst 3 SDS
· DNELs
646-06-0 1,3-dioxolane

Oral	DNEL Long term-systemic	1.31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	1.31 mg/kg bw/day (Consumer)
		2.62 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	4.52 mg/m ³ (Consumer)
		18.15 mg/m ³ (Worker)

67-63-0 propan-2-ol

Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	319 mg/kg bw/day (Consumer)
		888 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	89 mg/m ³ (Consumer)
		500 mg/m ³ (Worker)

78-93-3 butanone

Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer)
		1161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m ³ (Consumer)
		600 mg/m ³ (Worker)

141-43-5 2-aminoethanol

Oral	DNEL Long term-systemic	1.5 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	1.5 mg/kg bw/day (Consumer)
		3 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	0.18 mg/m ³ (Consumer)
		1 mg/m ³ (Worker)
	DNEL Long term-local	0.28 mg/m ³ (Consumer)
		0.51 mg/m ³ (Worker)

· Ingredients with biological limit values:
78-93-3 butanone

BMGV	70 µmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

General ventilation

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter ABEK/P2

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

Trade name: GRAFFITI REMOVER - PAINT REMOVER

(Contd. of page 5)

· Hand protection


Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm
· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Safety glasses



Tightly sealed goggles

· Body protection:

Use protective suit. (EN-13034/6)

Full skin covering antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

· Environmental exposure controls Use a suitable container to prevent environmental contamination.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties
· General Information

· Physical state	Aerosol
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	-44.5 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	0.7 Vol %
· Upper:	19.9 Vol %
· Flash point:	-97 °C
· Ignition Temperature	235 °C
· pH	Mixture is non-polar/aprotic.
· Viscosity:	
· Kinematic viscosity	Not determined.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

Trade name: GRAFFITI REMOVER - PAINT REMOVER

(Contd. of page 6)

· Dynamic:	Not determined
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	0.79 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	98.1 %
· Solids content:	52.9 %
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

Trade name: GRAFFITI REMOVER - PAINT REMOVER

(Contd. of page 7)

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	85042 mg/kg (Rat)
Inhalative	LC50 (4h)	73 mg/l (Rat)

646-06-0 1,3-dioxolane

Oral	LD50	>2000 mg/kg (Rat) (Acute Oral Toxicity)
Inhalative	LC50 (4h)	68.4 mg/l (Rat) (Acute Inhalation Toxicity)

67-63-0 propan-2-ol

Oral	LD50	5840 mg/kg (Rat)
Dermal	LD50	13900 mg/kg (Rabbit)
Inhalative	LC50 (4h)	>25 mg/l (Rat)
	LC50	>25 mg/L (Rat) (Acute Inhalation Toxicity)

78-93-3 butanone

Oral	LD50	>2193 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (Rabbit)
		5000 mg/kg (Rabbit)

141-43-5 2-aminoethanol

Oral	LD50	1515 mg/kg (Rat) (Acute Oral Toxicity)
Dermal	LD50	2881 mg/kg (Rabbit) (Acute Dermal Toxicity)
Inhalative	LC50 (4h)	1.3 mg/l (Rat) (Acute Inhalation Toxicity)

Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1%

Oral	LD50	>5000 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (Rabbit)
Inhalative	LC50 (4h)	4951 mg/l (Rat)

· **Skin corrosion/irritation** Causes skin irritation.

· **Serious eye damage/irritation** Causes serious eye irritation.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

78-93-3	butanone	List II
95-14-7	benzotriazole	List II

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

67-63-0 propan-2-ol

EC50	>100 mg/l (Bacteria)
------	----------------------

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

Trade name: GRAFFITI REMOVER - PAINT REMOVER

(Contd. of page 8)

LOEC (8 days)	1000 mg/l (Algae)
LC50 (96h)	9640 mg/l (Pimephales promelas)
LC50 (24h)	9714 mg/l (Daphnia magna)
78-93-3 butanone	
LC50 (96h)	2993 mg/l (Pimephales promelas)
EC50 (48h)	308 mg/l (Daphnia magna)
141-43-5 2-aminoethanol	
LC0 (96h)	150 mg/l (Fish)
LC100	500 mg/l (Fish)
NOEC (21 days)	0.85 mg/l (Daphnia magna)
EC50 (72h)	2.8 mg/l (Pseudokirchneriella subcapitata)
LC50 (96h)	349 mg/l (Cyprinus carpio)
EC50 (48h)	65 mg/l (Daphnia magna)
Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1%	
EL0 (48h)	1000 mg/l (Daphnia magna)
EL0 (72h)	1000 mg/l (Pseudokirchneriella subcapitata)
LL0 (96h)	1000 mg/l (Onc)

- **12.2 Persistence and degradability** Not easily biodegradable
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

HP3	Flammable
-----	-----------

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---------------------------------------|---------------------|
| · 14.1 UN number or ID number | |
| · ADR, ADN, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name | |
| · ADR, ADN | UN1950 AEROSOLS |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

Trade name: GRAFFITI REMOVER - PAINT REMOVER

(Contd. of page 9)

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 2 5F Gases.
 · **Label** 2.1

· **ADN**

· **ADN/R Class:** 2 5F

· **IMDG, IATA**



· **Class** 2.1 Gases.
 · **Label** 2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user**

Warning: Gases.

· **Hazard identification number (Kemler code):**

-

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre:
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
 For AEROSOLS with a capacity above 1 litre:
 Segregation as for the appropriate subdivision of class 2.
 For WASTE AEROSOLS:
 Segregation as for the appropriate subdivision of class 2.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **Transport category**

2

· **Tunnel restriction code**

D

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

Trade name: GRAFFITI REMOVER - PAINT REMOVER

(Contd. of page 10)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

78-93-3 butanone

3

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 butanone

3

· National regulations:

· Breakdown regulations:

Class	Share in %
NK	75-<100

- VOC-CH 92.15 %
- VOC-EU 739.8 g/l
- Danish MAL Code 5-3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.01.2023

Version: 15 (replaces version 14)

Revision: 05.01.2023

Trade name: GRAFFITI REMOVER - PAINT REMOVER

(Contd. of page 11)

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008**

Physical and chemical properties: The classification is based on the results of the mixtures tested. Health hazards, Environmental hazards: The method of classification of mixtures based on the constituents of the mixture (sum formula).

· **Date of previous version:** 17.11.2022

· **Version number of previous version:** 14

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered. ***

GB

DISCLAIMER

The information contained in this sheet comes from reliable sources. It has been drawn up based on our knowledge at the time of the most recent update, as indicated. This information is intended as an aid to the user and should not be considered as a guarantee.

Conditions or methods of handling, storage, use or disposal of the product are outside our control, and we may not be held responsible for any loss, damage or expenses incurred as a result of, or in connection with, the latter.

All substances or mixtures can present unknown dangers and must be used with caution. We cannot guarantee that all dangers have been set out in an exhaustive manner.

This sheet has been drawn up for, and must be used for, this product only. If the product is used as a component in another product, the information given with it may not be applicable.

This sheet does not under any circumstances exempt the user from complying with all laws, regulations and administrative requirements related to the product, health and safety, and the protection of human health and the environment.