

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.04.2023

Version: 27 (replaces version 26)

Revision: 05.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** TRIG-A-CAP® ASPHALT
- **Article number:** 6301100000 UFI : HQM5-G09W-F009-9QV5
- **Relevant identified uses of the substance or mixture and uses advised against -**
- **Application of the substance / the mixture**
Surface protection
Aerosol coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
A.M.P.E.R.E. SYSTEM
3 rue Antoine Balard - Z.I. du Vert Galant
95310 Saint-Ouen-l'Aumône - FRANCE
Tel: + 33 1 34 64 72 72 / Fax: +33 1 30 37 55 17
fds@amperesystem.com
- **Emergency telephone number:** UK : National Poisons Information Service - 0344 892 0111
Ireland : National Poisons Information Centre - Beaumont Hospital - PO Box 1297 Beaumont Road 9 Dublin :
+353 1 809 2566 (Healthcare professionals-24/7) - +353 1 809 2166 (public, 8am - 10pm, 7/7)

SECTION 2: Hazards identification

- **Classification of the substance or mixture**



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Label elements**

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS09

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Hydrocarbons, C9, aromatics

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.04.2023

Version: 27 (replaces version 26)

Revision: 05.04.2023

Trade name: TRIG-A-CAP® ASPHALT

(Contd. of page 1)

butanone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

· Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****· Mixtures****· Description:** Active substance with propellant**· Dangerous components:**

CAS: 128601-23-0 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Consisting of: 98-82-8 isopropylbenzene (<2%); 71-43-2 benzene (<0.1%) Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	10-<25%
CAS: 8052-42-4 EINECS: 232-490-9 Reg.nr.: 01-2119480172-44	Asphalt	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<25%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	10-<25%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: UK-01-1376353405-7-0007	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	2.5-<10%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.04.2023

Version: 27 (replaces version 26)

Revision: 05.04.2023

Trade name: TRIG-A-CAP® ASPHALT

(Contd. of page 2)

EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	2.5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8), Note K) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	2.5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<2.5%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	0.1-<1%

Additional information:

Aerosols and containers fitted with a solid atomizer containing substances or mixtures classified as hazardous by aspiration shall not be labelled for that hazard.

The text of the hazard statements mentioned here can be found in chapter 16.

SECTION 4: First aid measures**Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.04.2023

Version: 27 (replaces version 26)

Revision: 05.04.2023

Trade name: TRIG-A-CAP® ASPHALT

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**· Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**· Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****· Control parameters****· Ingredients with limit values that require monitoring at the workplace:****8052-42-4 Asphalt**

WEL	Short-term value: 10 mg/m ³ Long-term value: 5 mg/m ³
-----	--

74-98-6 propane

OEL	Long-term value: 1800 mg/m ³ , 1000 ppm Additioneel ingevuld tbv klant voor Hfdst3 SDS
-----	--

78-93-3 butanone

WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
-----	---

106-97-8 butane (containing < 0.1% butadiene (203-450-8), Note K)

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K)

OEL	Long-term value: 2400 mg/m ³ , 1000 ppm Additioneel ingevuld obv klant voor Hfdst 3 SDS
-----	---

64-17-5 ethanol

WEL	Long-term value: 1920 mg/m ³ , 1000 ppm
-----	--

· DNELs**128601-23-0 Hydrocarbons,C9,aromatics**

Oral	DNEL Long term-systemic	11 mg/kg bw/day (Consumer)
------	-------------------------	----------------------------

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.04.2023

Version: 27 (replaces version 26)

Revision: 05.04.2023

Trade name: TRIG-A-CAP® ASPHALT

(Contd. of page 4)

Dermal	DNEL Long term-systemic	11 mg/kg bw/day (Consumer) 25 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	32 mg/m ³ (Consumer) 100 mg/m ³ (Worker)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	DNEL Long term-systemic	125 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	125 mg/kg bw/day (Consumer) 208 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	185 mg/m ³ (Consumer) 871 mg/m ³ (Worker)
78-93-3 butanone		
Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer) 1161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m ³ (Consumer) 600 mg/m ³ (Worker)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer) 773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m ³ (Consumer) 2035 mg/m ³ (Worker)

· Ingredients with biological limit values:**78-93-3 butanone**

BMGV 70 µmol/L
Medium: urine
Sampling time: post shift
Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

General ventilation

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

· **Hand protection**

Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.04.2023

Version: 27 (replaces version 26)

Revision: 05.04.2023

Trade name: TRIG-A-CAP® ASPHALT

(Contd. of page 5)

application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

- **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye/face protection**

Safety glasses



Tightly sealed goggles

- **Body protection:**

Use protective suit. (EN-13034/6)

Full skin covering antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

- **Environmental exposure controls** Use a suitable container to prevent environmental contamination.

*

SECTION 9: Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Aerosol

- **Colour:**

According to product specification

- **Odour:**

Characteristic

- **Odour threshold:**

Not determined.

- **Melting point/freezing point:**

Undetermined.

- **Boiling point or initial boiling point and boiling range**

-44.5 °C

- **Flammability**

Not applicable.

- **Lower and upper explosion limit**

- **Lower:**

0.6 Vol %

- **Upper:**

11.5 Vol %

- **Flash point:**

-97 °C

- **Ignition Temperature**

270 °C (64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Mixture is non-polar/aprotic.

- **pH**

- **Viscosity:**

- **Kinematic viscosity**

Not determined.

- **Kinematic viscosity**

- **Dynamic:**

7.500 - 10.500 Brookfield sp3 6 rpm

4.000 - 6000 Brookfield sp3 12 rpm

- **Solubility**

- **water:**

Not miscible or difficult to mix.

- **Partition coefficient n-octanol/water (log value)**

Not determined.

- **Vapour pressure at 20 °C:**

4900 hPa

- **Vapour Pressure at 50 °C:**

8500 hPa

- **Density and/or relative density**

- **Density at 20 °C:**

0.748 g/cm³

- **Relative density**

Not determined.

- **Vapour density**

Not determined.

- **Other information**

- **Appearance:**

- **Form:**

Aerosol

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.04.2023

Version: 27 (replaces version 26)

Revision: 05.04.2023

Trade name: TRIG-A-CAP® ASPHALT

(Contd. of page 6)

· **Important information on protection of health and environment, and on safety.**

- **Ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Solvent content:**
- **Organic solvents:** 74.8 %
- **Solids content:** 25.2 %
- **Change in condition**
- **Evaporation rate** Not applicable.

· **Information with regard to physical hazard classes**

- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Extremely flammable aerosol. Pressurised container: May burst if heated.
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

128601-23-0 Hydrocarbons, C9, aromatics

Oral	LD50	3492 mg/kg (Rat)
Dermal	LD50	>3160 mg/kg (Rabbit)
Inhalative	LC50 (4h)	>6193 mg/l (Rat) (Acute Inhalation Toxicity)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	LD50	>5000 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (Rabbit)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.04.2023

Version: 27 (replaces version 26)

Revision: 05.04.2023

Trade name: TRIG-A-CAP® ASPHALT

(Contd. of page 7)

Inhalative	LC50 (4h)	4951 mg/m3 (Rat)
78-93-3 butanone		
Oral	LD50	>2193 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (Rabbit)
		5000 mg/kg (Rabbit)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>5840 mg/kg (Rat)
Dermal	LD50	>2920 mg/kg (Rabbit)
Inhalative	LC50 (4h)	>25 mg/l (Rat)
<ul style="list-style-type: none"> · Serious eye damage/irritation Causes serious eye irritation. · STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness. · Aspiration hazard May be fatal if swallowed and enters airways. · Information on other hazards 		
· Endocrine disrupting properties		
78-93-3	butanone	List II

*

SECTION 12: Ecological information· **Toxicity**· **Aquatic toxicity:****128601-23-0 Hydrocarbons, C9, aromatics**

NOELR (72h)	1 mg/l (Pseudokirchneriella subcapitata)
EL50 (48h)	3.2 mg/l (Daphnia magna)
LL50 (96h)	9.2 mg/l (Oncorhynchus mykiss)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

EL0 (48h)	1000 mg/l (Daphnia magna)
NOELR (72h)	100 mg/l (Pseudokirchneriella subcapitata)
EL50 (72h)	>1000 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	>1000 mg/l (Onc)

78-93-3 butanone

LC50 (96h)	2993 mg/l (Pimephales promelas)
EC50 (48h)	308 mg/l (Daphnia magna)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

NOELR (72h)	3 mg/l (Pseudokirchneriella subcapitata)
EL50 (48h)	3 mg/l (Daphnia magna)
EL50 (72h)	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	11.4 mg/l (Oncorhynchus mykiss)
NOEC (21 days)	0.17 mg/l (Daphnia magna)
LOEC (21 days)	0.32 mg/l (Daphnia magna)

- **Persistence and degradability** Not easily biodegradable
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **Other adverse effects**
- **Remark:** Toxic for fish

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.04.2023

Version: 27 (replaces version 26)

Revision: 05.04.2023

Trade name: TRIG-A-CAP® ASPHALT

(Contd. of page 8)

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms

SECTION 13: Disposal considerations

· **Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **UN number or ID number**

UN1950

· **ADR, ADN, IMDG, IATA**

· **UN proper shipping name**

· **ADR, ADN**

UN1950 AEROSOLS, ENVIRONMENTALLY
HAZARDOUS

· **IMDG**

AEROSOLS, MARINE POLLUTANT

· **IATA**

AEROSOLS, flammable

· **Transport hazard class(es)**

· **ADR**



· **Class**

2 5F Gases.

· **Label**

2.1

· **ADN**

· **ADN/R Class:**

2 5F

· **IMDG**



· **Class**

2.1 Gases.

· **Label**

2.1

· **IATA**



· **Class**

2.1 Gases.

· **Label**

2.1

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.04.2023

Version: 27 (replaces version 26)

Revision: 05.04.2023

Trade name: TRIG-A-CAP® ASPHALT

(Contd. of page 9)

· Packing group · ADR, IMDG, IATA	Void
· Environmental hazards: · Marine pollutant: · Special marking (ADR):	Product contains environmentally hazardous substances: Symbol (fish and tree) Symbol (fish and tree)
· Special precautions for user · Hazard identification number (Kemler code): - · EMS Number: · Stowage Code	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

*

SECTION 15: Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- National regulations:
- Breakdown regulations:

Class	Share in %
NK	50-<75

(Contd. on page 11)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 05.04.2023

Version: 27 (replaces version 26)

Revision: 05.04.2023

Trade name: TRIG-A-CAP® ASPHALT

(Contd. of page 10)

- **VOC-CH** 74.76 %
- **VOC-EU** 559.2 g/l
- **Danish MAL Code** 5-3
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008**

Physical and chemical properties: The classification is based on the results of the mixtures tested. Health hazards, Environmental hazards: The method of classification of mixtures based on the constituents of the mixture (sum formula).

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
 DNEL: Derived No-Effect Level (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

- *** Data compared to the previous version altered. ***

GB

DISCLAIMER

The information contained in this sheet comes from reliable sources. It has been drawn up based on our knowledge at the time of the most recent update, as indicated. This information is intended as an aid to the user and should not be considered as a guarantee.

Conditions or methods of handling, storage, use or disposal of the product are outside our control, and we may not be held responsible for any loss, damage or expenses incurred as a result of, or in connection with, the latter.

All substances or mixtures can present unknown dangers and must be used with caution. We cannot guarantee that all dangers have been set out in an exhaustive manner.

This sheet has been drawn up for, and must be used for, this product only. If the product is used as a component in another product, the information given with it may not be applicable.

This sheet does not under any circumstances exempt the user from complying with all laws, regulations and administrative requirements related to the product, health and safety, and the protection of human health and the environment.