

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

Product code : 632001305 UFI : 7WN5-J0YF-R007-JH12

1.2. Relevant identified uses of the substance or mixture and uses advised against

As spray

PAINT

1.3. Details of the supplier of the safety data sheet

Registered company name : A.M.P.E.R.E. System.

Address : 3 Rue Antoine Balard - P.A. du Vert Galant .95310.SAINT OUEN L'AUMONE.FRANCE.

Telephone : +33 1 34 64 72 72. Fax : +33 1 30 37 55 17.

fds@amperesystem.com

http://www.amperesystem.com

1.4. Emergency telephone number :

UK : National Poisons Information Service - 0344 892 0111

Ireland : National Poisons Information Centre - Beaumont Hospital - PO Box 1297 Beaumont Road 9 Dublin :

+353 1 809 2566 (Healthcare professionals-24/7) - +353 1 809 2166 (public, 8am - 10pm, 7/7)

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

May produce an allergic reaction (EUH208).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Specific target organ toxicity (repeated exposure), Category 2 (STOT RE 2, H373).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

The propellant gas is not taken into account when determining the health and environmental classification of the mixture.

2.2. Label elements

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05



GHS09



GHS08



GHS02



GHS07

Signal Word :

DANGER

Product identifiers :

606-001-00-8

EC 292-694-9

603-108-00-1

ACETONE

AROMATIC HYDROCARBONS, C8

2-METHYLPROPAN-1-OL

Additional labeling :

EUH208

Contains MALEIC ANHYDRIDE. May produce an allergic reaction.

Hazard statements :

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H315

Causes skin irritation.

H318

Causes serious eye damage.

H335

May cause respiratory irritation.

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure (if inhaled).
H411	Toxic to aquatic life with long lasting effects.
Precautionary statements - General :	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Precautionary statements - Prevention :	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/ ...
Precautionary statements - Response :	
P302 + P352	IF ON SKIN: Wash with plenty of water/...
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/... if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
Precautionary statements - Storage :	
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Precautionary statements - Disposal :	
P501	Dispose of contents / container in accordance with local / regional / national / international regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances >= 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	Classification (EC) 1272/2008	Note	%
CAS: 115-10-6 EC: 204-065-8 REACH: 01-2119472128-37-XXXX	GHS02 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	25 <= x % < 50
DIMETHYL ETHER INDEX: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 REACH: 01-2119471330-49-XXXX	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH:066	[1]	10 <= x % < 25
ACETONE CAS: 90989-38-1 EC: 292-694-9 REACH: 01-2119486136-34-XXXX	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373	J	2.5 <= x % < 10
AROMATIC HYDROCARBONS, C8			

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

INDEX: 030-011-00-6 CAS: 7779-90-0 EC: 231-944-3 REACH: 01-2119485044-40-XXXX TRIZINC BIS(ORTHOPHOSPHATE)	GHS09 Wng Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		0 <= x % < 2.5
INDEX: 603-108-00-1 CAS: 78-83-1 EC: 201-148-0 REACH: 01-2119484609-23-XXXX 2-METHYLPROPAN-1-OL	GHS02, GHS05, GHS07 Dgr Flam. Liq. 3, H226 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336	[1]	0 <= x % < 2.5
CAS: 77-99-6 EC: 201-074-9 REACH: 0-2119486799-10 PROPYLIDYNETRIMETHANOL	GHS08 Wng Repr. 2, H361fd	[2]	0 <= x % < 2.5
INDEX: 603-001-00-X CAS: 67-56-1 EC: 200-659-6 REACH: 01-2119433307-44-XXXX METHANOL	GHS02, GHS06, GHS08 Dgr Flam. Liq. 2, H225 Acute Tox. 3, H331 Acute Tox. 3, H311 Acute Tox. 3, H301 STOT SE 1, H370	[1] [XVII]	0 <= x % < 2.5
INDEX: 607-096-00-9 CAS: 108-31-6 EC: 203-571-6 MALEIC ANHYDRIDE	GHS07, GHS05, GHS08 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Resp. Sens. 1, H334 STOT RE 1, H372 EUH:071	[1]	0 <= x % < 2.5

Specific concentration limits:

Identification	Specific concentration limits	ATE
CAS: 90989-38-1 EC: 292-694-9 REACH: 01-2119486136-34-XXXX AROMATIC HYDROCARBONS, C8		dermal: ATE = 12126 mg/kg BW oral: ATE = 3523 mg/kg BW
INDEX: 603-001-00-X CAS: 67-56-1 EC: 200-659-6 REACH: 01-2119433307-44-XXXX METHANOL	STOT SE 1 (Cut) : H370 C>= 10% STOT SE 2: H371 3% <= C < 10% STOT SE 1 (Oral) : H370 C>= 10% STOT SE 2: H371 3% <= C < 10% STOT SE 1 (Inh) : H370 C>= 10% STOT SE 2: H371 3% <= C < 10%	
INDEX: 607-096-00-9 CAS: 108-31-6 EC: 203-571-6 MALEIC ANHYDRIDE	Skin Sens. 1A: H317 C>= 0.001%	

Information on ingredients :

(Full text of H-phrases: see section 16)

[XVII] Restricted substance under Regulation (EC) No. 1907/2006 (REACH), Annex XVII.

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

[7] Propellant gas

Note J: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS 200-753-7).

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

Pressurized container

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

Consult the safety measures listed under headings 7 and 8.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

-

Do not breathe vapors

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not inhale vapours.

Do not breathe in aerosols.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid eye contact with this mixture at all times.

Avoid exposure - obtain special instructions before use.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

Do not pierce or burn even after use.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

It's to recommend to indicate the stock of spray. Sprays must be surrounded by a metal grating or by wall to avoid the projections of sprays.

Store between +5°C and +30°C

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m ³ :	VME-ppm :	VLE-mg/m ³ :	VLE-ppm :	Notes :
115-10-6	1920	1000	-	-	-
67-64-1	1210	500	-	-	-
67-56-1	260	200	-	-	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
67-64-1	500 ppm	750 ppm		A4; BEI	
78-83-1	50 ppm				
67-56-1	200 ppm	250 ppm		Skin; BEI	
108-31-6	0.01 (IFV) mg/m ³			SEN; A4	

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME :	VME :	Excess	Notes
115-10-6		1000 ppm 1900 mg/m ³		8(II)
67-64-1		500 ppm 1200 mg/m ³		2(I)
78-83-1		100 ppm 310 mg/m ³		1(I)
67-56-1		200 ppm 270 mg/m ³		4(II)
108-31-6		0.02 ppm 0.081 mg/m ³		1;=2.5=(I)

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m ³ :	VLE-ppm :	VLE-mg/m ³ :	Notes :	TMP No :
115-10-6	1000	1920	-	-	-	-
67-64-1	500	1210	1000	2420	-	84
78-83-1	50	150	-	-	-	84
67-56-1	200	260	1000	1300	(12)	84
108-31-6	-	-	-	1	ALL	66

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
115-10-6	400 ppm 766 mg/m ³	500 ppm 958 mg/m ³			
67-64-1	500 ppm 1210 mg/m ³	1500 ppm 3620 mg/m ³			

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

78-83-1	50 ppm 154 mg/m ³	75 ppm 231 mg/m ³			
67-56-1	200 ppm 266 mg/m ³	250 ppm 333 mg/m ³		Sk	
108-31-6	1 mg/m ³	3 mg/m ³		Sen	

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

AROMATIC HYDROCARBONS, C8 (CAS: 90989-38-1)

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
180 mg/kg body weight/day

Inhalation.
Short term systemic effects.
289 mg of substance/m³

Inhalation.
Long term systemic effects.
77 mg of substance/m³

Consumers.

Ingestion.
Long term systemic effects.
1.6 mg/kg body weight/day

Dermal contact.
Long term systemic effects.
108 mg/kg body weight/day

Inhalation.
Short term systemic effects.
174 mg of substance/m³

Inhalation.
Long term systemic effects.
14.8 mg of substance/m³

ACETONE (CAS: 67-64-1)

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:

Workers.

Dermal contact.
Long term systemic effects.
186 mg/kg body weight/day

Inhalation.
Long term systemic effects.
1210 mg of substance/m³

Inhalation.
Short term local effects.
2420 mg of substance/m³

Consumers.

Ingestion.
Long term systemic effects.
62 mg/kg body weight/day

Dermal contact.
Long term systemic effects.
62 mg/kg body weight/day

Inhalation.

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

Potential health effects:

DNEL :

Long term systemic effects.

200 mg of substance/m³**Predicted no effect concentration (PNEC):**

AROMATIC HYDROCARBONS, C8 (CAS: 90989-38-1)

Environmental compartment:

PNEC :

Soil.

2.31 mg/kg

Environmental compartment:

PNEC :

Fresh water.

0.327 mg/l

Environmental compartment:

PNEC :

Fresh water sediment.

12.46 mg/kg

Environmental compartment:

PNEC :

Waste water treatment plant.

6.58 mg/l

ACETONE (CAS: 67-64-1)

Environmental compartment:

PNEC :

Soil.

29.5 mg/kg

Environmental compartment:

PNEC :

Fresh water.

10.6 mg/l

Environmental compartment:

PNEC :

Sea water.

1.06 mg/l

Environmental compartment:

PNEC :

Intermittent waste water.

21 mg/l

Environmental compartment:

PNEC :

Waste water treatment plant.

100 mg/l

Environmental compartment:

PNEC :

Fresh water predators (oral).

3.04 mg/kg

Environmental compartment:

PNEC :

Salt water predators (oral).

30.4 mg/kg

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)
- Butyl Rubber (Isobutylene-isoprene copolymer)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149/A1.

Category :

- FFP1
- FFP3

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)
- A3 (Brown)

Particle filter according to standard EN143 :

- P1 (White)
- P3 (White)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Spray : Spray : Pressure to 20°C : 4.0 bars ± 1 bar

Physical state

Physical state : Viscous liquid.
Spray.

Colour

COPPER

Odour

Odour threshold : Not stated.

Melting point

Melting point/melting range : Not relevant.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not relevant.

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

Flash point

Flash point interval : Not relevant.

Auto-ignition temperature

Self-ignition temperature : Not relevant.

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

Decomposition temperature

Decomposition point/decomposition range : Not relevant.

pH

pH (aqueous solution) : Not stated.

pH : Not relevant.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Insoluble.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50 °C) : Below 110 kPa (1.10 bar).

Density and/or relative density

Density : > 1

Relative vapour density

Vapour density : Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

Aerosols

Chemical combustion heat : >= 30 kJ/g.

Gases under pressure

CAS 115-10-6 : colorless liquid propellant / Explored characteristics : 3.3% - 26.20% volume

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

Avoid storing more than 2 years

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat

Keep away from oxydizing agent, acids or base

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1. Substances

Acute toxicity :

AROMATIC HYDROCARBONS, C8 (CAS: 90989-38-1)

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

Oral route :	LD50 = 3523 mg/kg bodyweight/day Species : Rat
Dermal route :	LD50 = 12126 mg/kg bodyweight/day Species : Rat
Inhalation route (Vapours) :	LC50 27124 Duration of exposure : 4 h

11.1.2. Mixture

Skin corrosion/skin irritation :

Irritating to skin.

Serious damage to eyes/eye irritation :

Causes serious eye damage

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

May cause respiratory irritation.

Specific target organ systemic toxicity - repeated exposure :

Suspected risk of serious organ damage through repeated or prolonged exposure.

11.2. Information on other hazards

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

AROMATIC HYDROCARBONS, C8 (CAS: 90989-38-1)

Fish toxicity : LC50 = 2.6 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 2.2 mg/l
Duration of exposure : 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

AROMATIC HYDROCARBONS, C8 (CAS: 90989-38-1)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

12.3.1. Substances

AROMATIC HYDROCARBONS, C8 (CAS: 90989-38-1)

Octanol/water partition coefficient : log K_{ow} = 3.2

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 1 : Slightly hazardous for water.

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.
Do not pierce or burn even after use.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.
Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2020 [40-20] - ICAO/IATA 2023 [64]).

14.1. UN number or ID number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification :



2.1

14.4. Packing group

-

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D

IMDG	Class	2 ^e Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69

IATA	Class	2 ^e Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A802	E0
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

Marine pollutant (IMDG 3.1.2.9):(trizinc bis(orthophosphate))

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

Container information:

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):
<https://echa.europa.eu/substances-restricted-under-reach>.

Explosives precursors :

The mixture contains at least one substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors:

- Acetone (CAS 67-64-1)

The acquisition, introduction, possession or use of this restricted explosive precursor by members of the general public is subject to the reporting obligations.

Particular provisions :

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBWs) :

WGK 1 : Slightly hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H370	Causes damage to organs .
H372	Causes damage to organs through prolonged or repeated exposure .
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

PROFESSIONAL PAINT WHITE HIGH TEMPERATURE

EUH071

Corrosive to the respiratory tract.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS05 : Corrosion

GHS07 : Exclamation mark

GHS08 : Health hazard

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.

DISCLAIMER

The information contained in this sheet comes from reliable sources. It has been drawn up based on our knowledge at the time of the most recent update, as indicated. This information is intended as an aid to the user and should not be considered as a guarantee.

Conditions or methods of handling, storage, use or disposal of the product are outside our control, and we may not be held responsible for any loss, damage or expenses incurred as a result of, or in connection with, the latter.

All substances or mixtures can present unknown dangers and must be used with caution. We cannot guarantee that all dangers have been set out in an exhaustive manner.

This sheet has been drawn up for, and must be used for, this product only. If the product is used as a component in another product, the information given with it may not be applicable.

This sheet does not under any circumstances exempt the user from complying with all laws, regulations and administrative requirements related to the product, health and safety, and the protection of human health and the environment.