Version number 4 (replaces version 3) Printing date 07.12.2022 Revision: 21.04.2022

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name: A.M.P.E.R.E UNIVERSAL MARKER® FLUO

Article number: 630702101+, 630703101+, 630703201+, 630704001+, 630705101+, 630706101+ 10747, 10750, 10752, 10754, 10757, 10759 / UFI: 6PP5-4061-G00P-HK8N

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Lacquer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

A.M.P.E.R.E. SYSTEM Tel: + 33 1 34 64 72 72 3 rue Antoine Balard Fax: +33 1 30 37 55 17 fds@amperesystem.com

Z.I. du Vert Galant 95310 Saint-Ouen-I'Aumône

**FRANCE** 

· Further information obtainable from: Customer Service

- 1.4 Emergency telephone number: UK: National Poisons Information Service 0344 892 0111
- · Ireland: National Poisons Information Centre Beaumont Hospital PO Box 1297 Beaumont Road 9 Dublin: +353 1 809 2566 (Healthcare professionals-24/7) - +353 1 809 2166 (public, 8am - 10pm, 7/7).

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)

Printing date 07.12.2022 Version number 4 (replaces version 3) Revision: 21.04.2022

#### Trade name: A.M.P.E.R.E UNIVERSAL MARKER® FLUO

		(Contd. of page 1)	
P210	Keep away from heat, hot surfaces,	sparks, open flames and other ignition sources. No smoking.	

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

*P501* Dispose of contents / container in accordance with regional regulations.

#### · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- $\cdot$  **PBT:** Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- . 3 2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

CAS: 64742-89-8	Solvent naphtha (petroleum), light aliph.	20-<25%
CAS: 04742-89-8 EINECS: 265-192-2 Index number: 649-267-00-0 Reg.nr.: 01-2119537181-47	& Asp. Tox. 1, H304	
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8))  Flam. Gas IA, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336  EUH066	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas IA, H220 Press. Gas (Comp.), H280	5-<10%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336	2.5-<5%

GB

Printing date 07.12.2022 Version number 4 (replaces version 3) Revision: 21.04.2022

Trade name: A.M.P.E.R.E UNIVERSAL MARKER® FLUO

		(Contd. of page 2)
CAS: 13463-67-7	titanium dioxide	<2.5%
EINECS: 236-675-5	<b>&amp;</b> Carc. 2, H351	
Index number: 022-006-00-2		
Reg.nr.: 01-2119489379-17		
CAS: 3068-39-1	3,6-bis(ethylamino)-9-[2-(methoxycarbonyl)phenyl]-2,7-	<b>≤</b> 0.5%
EINECS: 221-326-1	dimethylxanthylium chloride	
	♠ Acute Tox. 2, H330	
	Eye Dam. 1, H318	
	Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410	
	(M=1)	
	♠ Acute Tox. 4, H302; Skin Sens. 1, H317	

#### · Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

 ${\it Ensure \ adequate \ ventilation}.$ 

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 07.12.2022 Version number 4 (replaces version 3) Revision: 21.04.2022

Trade name: A.M.P.E.R.E UNIVERSAL MARKER® FLUO

See Section 13 for disposal information.

(Contd. of page 3)

### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

No special measures required.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ü		imit values that require monitoring at the workplace:		
106-97-8 butane (containing < 0,1 % butadiene (203-450-8))				
WEL Short-term value: 1810 mg/m³, 750 ppm				
Long-term value: 1450 mg/m³, 600 ppm				
		re than 0.1% of buta-1.3-diene)		
141-78-6 e	-			
		value: 1468 mg/m³, 400 ppm		
		value: 734 mg/m³, 200 ppm um dioxide		
		value: 10* 4** mg/m³ able **respirable		
		uote respiratie		
DNELs	.1 1			
141-78-6				
		4.5 mg/kg /per day (Consumer, longterm systemic)		
Dermal		63 mg/kg /per day (Worker, longterm systemic)		
		37 mg/kg /per day (Consumer, longterm systemic)		
Inhalative	DNEL	734 mg/m3 /200 ppm (Worker, longterm systemic)		
	DNEL	1468 mg/m3 /400 ppm (Worker, acure systemic)		
	DNEL	734 mg/m3 /200 ppm (Worker, longterm local)		
	DNEL	1468 mg/m3 /400 ppm (Worker, acute local)		
	DNEL	367 mg/m3 /100 ppm (Consumer, longterm systemic)		
	DNEL	734 mg/m3 /200 ppm (Consumer; acute systemic)		
	DNEL	367 mg/m3 /100 ppm (Consumer, longterm local)		
	DNEL	734 mg/m3 /200 ppm (Consumer, acute local)		
Hydrocarl	bons, Co	6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	DNEL	1301 mg/kg /per day (Consumer, longterm systemic)		
Dermal	DNEL	13964 mg/kg /per day (Worker, longterm systemic)		
	DNEL	1377 mg/kg /per day (Consumer, longterm systemic)		
		ı	(Contd. on page	

id. on page

Printing date 07.12.2022 Version number 4 (replaces version 3) Revision: 21.04.2022

Trade name: A.M.P.E.R.E UNIVERSAL MARKER® FLUO

(Contd. of page 4)

Inhalative DNEL 5306 mg/m3 (Worker, longterm systemic)
DNEL 1131 mg/m3 (Consumer, longterm systemic)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

- · Hand protection Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye/face protection Not required.

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

• **Lower:** 1.5 Vol % (106-97-8 butane (containing < 0,1 %

butadiene (203-450-8)))

· Upper: 10.9 Vol % (74-98-6 propane)

· Flash point: Not applicable, as aerosol.

• Ignition temperature: 365 °C (689 °F) (106-97-8 butane (containing < 0.1 %

butadiene (203-450-8)))

· Decomposition temperature: Not determined.

 $\cdot pH$  Mixture is non-soluble (in water).

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C (68 °F): 8300 hPa (6225.5 mm Hg) (74-98-6 propane)

· Density and/or relative density

Density at 20 °C (68 °F):
 Relative density
 Vapour density
 Not determined.
 Not determined.

(Contd. on page 6)

Printing date 07.12.2022 Version number 4 (replaces version 3) Revision: 21.04.2022

Trade name: A.M.P.E.R.E UNIVERSAL MARKER® FLUO

(Contd. of page 5)

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

• Explosive properties: Not determined.

· Solvent content:

· Organic solvents: 77.4 %
· VOC (EC) --619.0 g/l
· VOC-EU% 77.38 %
· Solids content: 22.5 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

Void· Oxidising gases · Gases under pressure Void · Flammable liquids Void · Flammable solids Void Void · Self-reactive substances and mixtures Void · Pyrophoric liquids · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable Void gases in contact with water

gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void
Desensitised explosives Void

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

ID/IC50	values	rolovant	for cla	ccification.

#### 141-78-6 ethyl acetate

Oral	LD50	>18000 mg/kg (rab)
Dermal	LD50	5620 mg/kg (rat)

(Contd. on page 7)

Printing date 07.12.2022 Version number 4 (replaces version 3) Revision: 21.04.2022

Trade name: A.M.P.E.R.E UNIVERSAL MARKER® FLUO

		(Contd. of page 6)		
Inhalative	LC50/4 h	1600 mg/m3 (rat)		
Hydrocarb	ons, C6-C7	, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>5000 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rat)		
Inhalative	<i>LC50 / 4 h</i>	>20 mg/m3 (rat)		
3068-39-1	3068-39-1 3,6-bis(ethylamino)-9-[2-(methoxycarbonyl)phenyl]-2,7-dimethylxanthylium chloride			
Oral	LD50	449 mg/kg (rat)		
Inhalative	LC50/4h	0.3  mg/l  (rat)		

- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC50 / 48 h 3 mg/l (daphnia magna / Wasserfloh)

EC50 / 72 h | 30 mg/l (Pseudokirchneriella subcapitata)

LC50 / 96 h 11.4 mg/l (oncorhynchus mykiss / Regenbogenforelle)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

GE

Printing date 07.12.2022 Version number 4 (replaces version 3) Revision: 21.04.2022

Trade name: A.M.P.E.R.E UNIVERSAL MARKER® FLUO

(Contd. of page 7)

SECTION 14: Transport information	
14.1 UN number or ID number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es) ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Gases.
EMS Number:	F- $D$ , $S$ - $U$
Stowage Code	SW1 Protected from sources of heat.
sion age cour	SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a capacity abo
	1 litre: Category B. For WASTE AEROSOLS: Category
	C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
	litre:
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities $(EQ)$	Code: E0
_	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D

(Contd. on page 9)

Printing date 07.12.2022 Version number 4 (replaces version 3) Revision: 21.04.2022

Trade name: A.M.P.E.R.E UNIVERSAL MARKER® FLUO

(Contd. of page 8)

· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity	
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1	

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

(Contd. on page 10)

Printing date 07.12.2022 Version number 4 (replace.

Version number 4 (replaces version 3) Revision: 21.04.2022

#### Trade name: A.M.P.E.R.E UNIVERSAL MARKER® FLUO

(Contd. of page 9) Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 2: Acute toxicity – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category I Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 \* \* Data compared to the previous version altered.

#### DISCLAIMER

The information contained in this sheet comes from reliable sources. It has been drawn up based on our knowledge at the time of the most recent update, as indicated. This information is intended as an aid to the user and should not be considered as a guarantee.

Conditions or methods of handling, storage, use or disposal of the product are outside our control, and we may not be held responsible for any loss, damage or expenses incurred as a result of, or in connection with, the latter.

All substances or mixtures can present unknown dangers and must be used with caution. We cannot guarantee that all dangers have been set out in an exhaustive manner. This sheet has been drawn up for, and must be used for, this product only. If the product is used as a component in another product, the information given with it may not be applicable.

This sheet does not under any circumstances exempt the user from complying with all laws, regulations and administrative requirements related to the product, health and safety, and the protection of human health and the environment.