

## Safety data sheet according to UK REACH

Printing date 27.11.2025

Version number 10 (replaces version 9)

Revision: 27.11.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

• **Trade name:** **TRIG-A-CAP® CHALK** : **Article number:** 30424000+, 630422000+, 630425000+, 630423100+, 630426000+, 630421000+, 630423000+ / 10684, 10681, 10685, 11567, 11568, 10680, 10682 : **UFI:** GQQ5-60FT-500M-FP8E

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### 1.3 Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### 1.4 Product category PC9a Coatings and paints, thinners, paint removers

#### 1.5 Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

#### 1.6 Application of the substance / the mixture Lacquer

#### 1.7 Details of the supplier of the safety data sheet

##### 1.7.1 Manufacturer/Supplier:

A.M.P.E.R.E. SYSTEM

3 rue Antoine Balard

Z.I. du Vert Galant

95310 Saint-Ouen-l'Aumône

FRANCE

Téléphone: + 33 1 34 64 72 72

fds@amperesystem.com

##### 1.8 Emergency telephone number:

UK : National Poisons Information Service - 0344 892 0111 : Ireland : National Poisons Information Centre - Beaumont Hospital - PO Box 1297 Beaumont Road 9 Dublin : +353 1 809 2566 (Healthcare professionals-24/7) - +353 1 809 2166 (public, 8am - 10pm, 7/7)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### 2.1.1 Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319

Causes serious eye irritation.

#### 2.2 Label elements

##### 2.2.1 Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

##### 2.2.2 Hazard pictograms



GHS02



GHS07

##### 2.2.3 Signal word Danger

##### 2.2.4 Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)

# Safety data sheet

## according to UK REACH

Printing date 27.11.2025

Version number 10 (replaces version 9)

Revision: 27.11.2025

### TRIG-A-CAP® CHALK

(Contd. of page 1)

H319 Causes serious eye irritation.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

#### · Additional information:

EUH208 Contains 2-Propenoic acid, 2-methyl-, 2-(dimethylamino)ethyl ester, polymer with butyl 2-propenoate, compds. with polyethylene glycol hydrogen maleate C9-11-alkyl ethers, Fatty acids, C18-unsatd., trimers, compds. with oleylamine, Fatty acids, tall-oil, compds. with oleylamine, Polyamide. May produce an allergic reaction.

Buildup of explosive mixtures possible without sufficient ventilation.

#### · 2.3 Other hazards

#### · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### · 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	25-<50%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	<2.5%

(Contd. on page 3)

# Safety data sheet according to UK REACH

Printing date 27.11.2025

Version number 10 (replaces version 9)

Revision: 27.11.2025

## TRIG-A-CAP® CHALK

(Contd. of page 2)

CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide substance with a Community workplace exposure limit	<2.5%
CAS: 1259547-09-5	2-Propenoic acid, 2-methyl-, 2-(dimethylamino)ethyl ester, polymer with butyl 2-propenoate, compds. with polyethylene glycol hydrogen maleate C9-11-alkyl ethers ⚠ Skin Sens. 1, H317	≥0.1-≤0.5%
CAS: 147900-93-4 Reg.nr.: 01-2119971821-33	Fatty acids, C18-unsatd., trimers, compds. with oleylamine ⚠ STOT RE 2, H373 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.25-≤0.5%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43	butanone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	≤0.5%
CAS: 85711-55-3 EINECS: 288-315-1 Reg.nr.: 01-2119974148-28	Fatty acids, tall-oil, compds. with oleylamine ⚠ STOT RE 2, H373 ⚠ Eye Dam. 1, H318 ⚠ Skin Sens. 1, H317	≥0.1-≤0.5%

### Additional information:

In accordance with the current Annex II of UK REACH, the concentration of the substances contained in the mixture are specified. For the classification of aerosols, the values used for calculation may differ.  
For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.  
Use fire extinguishing methods suitable to surrounding conditions.

### 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

### 5.3 Advice for firefighters -

- Protective equipment: Mouth respiratory protective device.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

# Safety data sheet according to UK REACH

Printing date 27.11.2025

Version number 10 (replaces version 9)

Revision: 27.11.2025

## TRIG-A-CAP® CHALK

(Contd. of page 3)

- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
No special measures required.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

##### 64-17-5 ethanol

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

##### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppmLong-term value: 766 mg/m<sup>3</sup>, 400 ppm

##### 141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m<sup>3</sup>, 400 ppmLong-term value: 734 mg/m<sup>3</sup>, 200 ppm

##### 106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppmLong-term value: 1450 mg/m<sup>3</sup>, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

##### 13463-67-7 titanium dioxide

WEL Long-term value: 10\* 4\*\* mg/m<sup>3</sup>

\*total inhalable \*\*respirable

##### 78-93-3 butanone

WEL Short-term value: 899 mg/m<sup>3</sup>, 300 ppmLong-term value: 600 mg/m<sup>3</sup>, 200 ppm

Sk, BMGV

### · DNELs

#### 64-17-5 ethanol

Oral DNEL 87 mg/kg /per day (Consumer, longterm systemic)

Dermal DNEL 343 mg/kg /per day (Worker, longterm systemic)

(Contd. on page 5)

## Safety data sheet according to UK REACH

Printing date 27.11.2025

Version number 10 (replaces version 9)

Revision: 27.11.2025

**TRIG-A-CAP® CHALK**

(Contd. of page 4)

<i>Inhalative</i>	<i>DNEL</i>	206 mg/kg /per day (Consumer, longterm systemic)
	<i>DNEL</i>	950 mg/m <sup>3</sup> (Worker, longterm systemic)
	<i>DNEL</i>	1900 mg/m <sup>3</sup> (Worker, acute local)
	<i>DNEL</i>	114 mg/m <sup>3</sup> (Consumer, longterm systemic)
	<i>DNEL</i>	950 mg/m <sup>3</sup> (Consumer, acute local)
<b>141-78-6 ethyl acetate</b>		
<i>Oral</i>	<i>DNEL</i>	4.5 mg/kg /per day (Consumer, longterm systemic)
<i>Dermal</i>	<i>DNEL</i>	63 mg/kg /per day (Worker, longterm systemic)
	<i>DNEL</i>	37 mg/kg /per day (Consumer, longterm systemic)
<i>Inhalative</i>	<i>DNEL</i>	734 mg/m <sup>3</sup> /200 ppm (Worker, longterm systemic)
	<i>DNEL</i>	1468 mg/m <sup>3</sup> /400 ppm (Worker, acute systemic)
	<i>DNEL</i>	734 mg/m <sup>3</sup> /200 ppm (Worker, longterm local)
	<i>DNEL</i>	1468 mg/m <sup>3</sup> /400 ppm (Worker, acute local)
	<i>DNEL</i>	367 mg/m <sup>3</sup> /100 ppm (Consumer, longterm systemic)
	<i>DNEL</i>	734 mg/m <sup>3</sup> /200 ppm (Consumer; acute systemic)
	<i>DNEL</i>	367 mg/m <sup>3</sup> /100 ppm (Consumer, longterm local)
	<i>DNEL</i>	734 mg/m <sup>3</sup> /200 ppm (Consumer, acute local)
<b>78-93-3 butanone</b>		
<i>Oral</i>	<i>DNEL</i>	31 mg/kg /per day (Consumer, longterm systemic)
<i>Dermal</i>	<i>DNEL</i>	1161 mg/kg /per day (Worker, longterm systemic)
	<i>DNEL</i>	412 mg/kg /per day (Consumer, longterm systemic)
<i>Inhalative</i>	<i>DNEL</i>	600 mg/m <sup>3</sup> (Worker, longterm systemic)
	<i>DNEL</i>	106 mg/m <sup>3</sup> (Consumer, longterm systemic)

· **PNECs****64-17-5 ethanol**

<i>PNEC</i>	0.96 mg/l (Freshwater)
<i>PNEC</i>	0.79 mg/l (Seawater)
<i>PNEC</i>	2.75 mg/l (Sporadic release)
<i>PNEC</i>	580 mg/l (Sewage treatment plant)
<i>PNEC</i>	3.6 mg/kg (Freshwater sediment)
<i>PNEC</i>	2.9 mg/kg (Seawater sediment)
<i>PNEC</i>	0.63 mg/kg (Soil)

**78-93-3 butanone**

<i>PNEC</i>	55.8 mg/l (Freshwater)
<i>PNEC</i>	55.8 mg/l (Seawater)
<i>PNEC</i>	55.8 mg/l (Sporadic release)
<i>PNEC</i>	709 mg/l (Sewage treatment plant)
<i>PNEC</i>	284.7 mg/kg (Freshwater sediment)
<i>PNEC</i>	284.7 mg/kg (Seawater sediment)

· **Ingredients with biological limit values:****78-93-3 butanone**

<i>BMGV</i>	70 µmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 6)

# Safety data sheet according to UK REACH

Printing date 27.11.2025

Version number 10 (replaces version 9)

Revision: 27.11.2025

## TRIG-A-CAP® CHALK

(Contd. of page 5)

- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.  
Avoid contact with the eyes.
- **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

- **Hand protection**



Protective gloves

- **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

- **Eye/face protection**



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Aerosol

- **Colour:**

According to product specification

- **Odour:**

Characteristic

- **Odour threshold:**

Not determined.

- **Melting point/freezing point:**

Undetermined.

- **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol.

- **Flammability**

Not applicable.

- **Lower and upper explosion limit**

- **Lower:**

3.3 Vol % (115-10-6 dimethyl ether)

(Contd. on page 7)

GB



## Safety data sheet according to UK REACH

Printing date 27.11.2025

Version number 10 (replaces version 9)

Revision: 27.11.2025

**TRIG-A-CAP® CHALK**

(Contd. of page 6)

· <b>Upper:</b>	26.2 Vol % (115-10-6 dimethyl ether)
· <b>Flash point:</b>	Not applicable, as aerosol.
· <b>Auto-ignition temperature:</b>	240 °C (464 °F) (115-10-6 dimethyl ether)
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Mixture is non-soluble (in water).
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>Dynamic:</b>	Not determined.
· <b>Solubility</b>	
· <b>water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure at 20 °C (68 °F):</b>	4000 hPa (3000.2 mm Hg) (115-10-6 dimethyl ether)
· <b>Vapour pressure at 50 °C (122 °F):</b>	11400 hPa (8550.7 mm Hg)
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C (68 °F):</b>	1 g/cm <sup>3</sup> (8.3 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.

· <b>9.2 Other information</b>	
· <b>Appearance:</b>	
· <b>Form:</b>	Aerosol
· <b>Important information on protection of health and environment, and on safety.</b>	
· <b>Explosive properties:</b>	Not determined.
· <b>Solvent content:</b>	
· <b>Organic solvents:</b>	66.9 %
· <b>VOC (EC)</b>	---
	605.0 g/l
· <b>VOC-EU%</b>	64.00 %
· <b>Solids content:</b>	31.7 %
· <b>Change in condition</b>	
· <b>Evaporation rate</b>	Not applicable.

· <b>Information with regard to physical hazard classes</b>	
· <b>Explosives</b>	Void
· <b>Flammable gases</b>	Void
· <b>Aerosols</b>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <b>Oxidising gases</b>	Void
· <b>Gases under pressure</b>	Void
· <b>Flammable liquids</b>	Void
· <b>Flammable solids</b>	Void
· <b>Self-reactive substances and mixtures</b>	Void
· <b>Pyrophoric liquids</b>	Void
· <b>Pyrophoric solids</b>	Void
· <b>Self-heating substances and mixtures</b>	Void
· <b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
· <b>Oxidising liquids</b>	Void
· <b>Oxidising solids</b>	Void
· <b>Organic peroxides</b>	Void
· <b>Corrosive to metals</b>	Void
· <b>Desensitised explosives</b>	Void

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.

(Contd. on page 8)

# Safety data sheet according to UK REACH

Printing date 27.11.2025

Version number 10 (replaces version 9)

Revision: 27.11.2025

## TRIG-A-CAP® CHALK

(Contd. of page 7)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

#### 64-17-5 ethanol

Oral	LD50	10470 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 / 4h	120 mg/l (rat)

#### 141-78-6 ethyl acetate

Oral	LD50	>18000 mg/kg (rab)
Dermal	LD50	5620 mg/kg (rat)
Inhalative	LC50 / 4 h	1600 mg/m3 (rat)

#### 78-93-3 butanone

Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	34 mg/m3 (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **11.2 Information on other hazards**

### · Endocrine disrupting properties

78-93-3	butanone	List II
---------	----------	---------

## SECTION 12: Ecological information

### · 12.1 Toxicity

#### · Aquatic toxicity:

#### 64-17-5 ethanol

LC50/96h	13000 mg/l (oncorhynchus mykiss)
EC50 / 48 h	12900 mg/l (algae)
LC50 / 48 h	12340 mg/l (daphnia magna)

#### 115-10-6 dimethyl ether

EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50 / 96 h	>4000 mg/l (fish)

#### 78-93-3 butanone

LC50 / 48 h	308 mg/l (daphnia magna)
LC50 / 72 h	1972 mg/l (Pseudokirchneriella Subcapitata)
LC50 / 96 h	2990 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 9)



# Safety data sheet

## according to UK REACH

Printing date 27.11.2025

Version number 10 (replaces version 9)

Revision: 27.11.2025

### TRIG-A-CAP® CHALK



(Contd. of page 8)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Dispose of packaging according to regulations on the disposal of packagings.

### SECTION 14: Transport information

- |   |                     |
|---|---------------------|
| · <b>14.1 UN number or ID number</b>  | UN1950              |
| · <b>ADR, IMDG, IATA</b>  |                     |
| · <b>14.2 UN proper shipping name</b>   | 1950 AEROSOLS       |
| · <b>ADR</b>  | AEROSOLS            |
| · <b>IMDG</b>   | AEROSOLS            |
| · <b>IATA</b>   | AEROSOLS, flammable |
| · <b>14.3 Transport hazard class(es)</b>  |                     |
| · <b>ADR</b>  |                     |
|  |                     |
| · <b>Class</b>  | 2.5F Gases.         |
| · <b>Label</b>  | 2.1                 |
| · <b>IMDG, IATA</b>   |                     |
|  |                     |
| · <b>Class</b>  | 2.1 Gases.          |
| · <b>Label</b>  | 2.1                 |
| · <b>14.4 Packing group</b>   | not regulated       |
| · <b>ADR, IMDG, IATA</b>  |                     |
| · <b>14.5 Environmental hazards:</b>  | Not applicable.     |
| · <b>14.6 Special precautions for user</b>  | Warning: Gases.     |
| · <b>Hazard identification number (Kemler code):</b>                                | -                   |

(Contd. on page 10)

## Safety data sheet according to UK REACH

Printing date 27.11.2025

Version number 10 (replaces version 9)

Revision: 27.11.2025

**TRIG-A-CAP® CHALK**

(Contd. of page 9)

· <b>EMS Number:</b>	F-D,S-U
· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

\*

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category P3a** FLAMMABLE AEROSOLS· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 11)

# Safety data sheet according to UK REACH

Printing date 27.11.2025

Version number 10 (replaces version 9)

Revision: 27.11.2025

**TRIG-A-CAP® CHALK**

(Contd. of page 10)

## SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

### • **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

### • **Classification according to Regulation (EC) No 1272/2008**

*Data is based on internal technical data and technical data from suppliers.*

*The propellant gas is not taken into account when determining the classification of the mixture for health and the environment.*

### • **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (UK REACH)
- PNEC: Predicted No-Effect Concentration (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Acute Tox. 4: Acute toxicity – Category 4
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

### • **\* Data compared to the previous version altered.**

GB

## DISCLAIMER

The information contained in this sheet comes from reliable sources. It has been drawn up based on our knowledge at the time of the most recent update, as indicated. This information is intended as an aid to the user and should not be considered as a guarantee.

Conditions or methods of handling, storage, use or disposal of the product are outside our control, and we may not be held responsible for any loss, damage or expenses incurred as a result of, or in connection with, the latter.

All substances or mixtures can present unknown dangers and must be used with caution. We cannot guarantee that all dangers have been set out in an exhaustive manner.

This sheet has been drawn up for, and must be used for, this product only. If the product is used as a component in another product, the information given with it may not be applicable.

This sheet does not under any circumstances exempt the user from complying with all laws, regulations and administrative requirements related to the product, health and safety, and the protection of human health and the environment.